# Air Conditioning

### **Product Information**

**MSZ-FH Inverter Heat Pump**Wall Mounted System

Making a
World of
Difference

**M** series



# MSZ-FH Inverter Heat Pump

Wall Mounted System

The MSZ-FH series is our most energy efficient M Series wall mounted unit to date.

These high efficiency models feature the Plasma Quad filter system. They also offer industry leading noise levels and have a distinctively styled front panel that not only looks appealing but also helps to make cleaning of the unit easier. Also incorporated is a '3D I-See Sensor', providing even temperature distribution and further reducing energy consumption.

#### **Key Features**

- Swing Vane Mode with Auto Vane Shutter
- Infra-red remote controller
- Econo Cool allows set temperature to be raised by 2°C without any loss of comfort and a 20% gain in energy efficiency
- Auto-Restart
- Quiet operation
- Auto-Changeover
- Hot Start draught prevention
- Plasma Quad filter system
- Quick clean design
- Replace Technology available
- I-See Sensor
- Electro anti-allergy filter



Air Conditioning | Heating Ventilation | Controls



## **Product Information**

# Air Conditioning

## **MSZ-FH Inverter Heat Pump** Wall Mounted System

Making a World of Difference









MSZ-FH - INDOOR UNITS		MSZ-FH25VE	MSZ-FH35VE
CAPACITY (kW)	Heating (nominal)	3.2 (1.8-5.5)	4.0 (1.0-6.3)
	Cooling (nominal)	2.5 (1.4-3.5)	3.5 (0.8-4.0)
	Heating (UK)	2.65 (1.49-4.57)	3.3 (0.8-5.2)
	Cooling (UK)	2.48 (1.38-3.47)	3.47 (0.79-3.97)
SHF (nominal & UK)		0.95	0.84
COP / EER (nominal)		5.52 / 5.15	5.00 / 4.27
SCOP / SEER (BSEN14825)		5.1 / 9.1	5.1 / 8.9
ErP ENERGY EFFICIENCY CLASS	Heating/Cooling	A+++ / A+++	A+++ / A+++
AIRFLOW (m³/min)	Heating - SLo-Lo-Mi-Hi-Shi	4.0-4.7-6.4-9.2-13.2	4.0-4.7-6.4-9.2-13.2
	Cooling - SLo-Lo-Mi-Hi-Shi	3.9-4.7-6.3-8.6-11.6	3.9-4.7-6.3-8.6-11.6
PIPE SIZE mm (in)	Gas	9.52 (3/8")	9.52 (3/8")
	Liquid	6.35 (1/4")	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling - Silent-Lo-Mi-Hi-Shi	20-24-29-36-44 / 20-23-29-36-42	21-24-29-36-44 / 21-24-29-36-42
SOUND POWER LEVEL (dBA)		58	58
DIMENSIONS (mm)	Width x Depth x Height	925 x 234 x 305	925 x 234 x 305
WEIGHT (kg)		13.5	13.5
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6
INTERCONNECTING CABLE No. CORES		4	4

MUZ-FH - OUTDOOR UNITS		MUZ-FH25VE	MUZ-FH35VE
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	49 / 46	50 / 49
SOUND POWER LEVEL (dBA)	Cooling	60	61
WEIGHT (kg)		37	37
DIMENSIONS (mm)	Width x Depth x Height	800 x 285 x 550	800 x 285 x 550
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	0.580 / 0.485	0.800 / 0.820
	Heating/Cooling (UK)	0.520 / 0.400	0.760 / 0.690
STARTING CURRENT (A)		2.9	3.9
SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX]		2.9 / 2.6 [9.6]	3.9 / 3.8 [9.6]
FUSE RATING (BS88) - HRC (A)		10	10
MAINS CABLE No. CORES		3	3
MAX PIPE LENGTH (m)		20	20
MAX HEIGHT DIFFERENCE (m)		12	12
CHARGE R410A (kg) - 7m		1.15	1.15



Telephone: 01707 282880

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thalland – Malaysia. OMtsubish liBectric Europe 2014. Misubish and Misubish iBectric are trademarks of Misubish liBectric Europe B.V. The company reserves the right to nake any variation in tachnical specification to the equipment described, or to withdraw or replace products without prior notification or public amountement. Misubish Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and branes may be trademarks or registered trademarks of their respective owners.













email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

to the environment Follow us @meuk\_les Follow us @green\_gateway

Mitsubishi Electric UK's commitment

**Gateway**