




R410A Mr Slim

Quick Reference Guide 2013



Model Reference	Capacity (kW)				Nominal & UK SHF	UK Sensible Cooling (kW)	System Power Input Heating / Cooling (kW)		Nominal COP / EER (BSEN14511)	SCOP / SEER (BSEN14825)	Airflow (m³/min) Lo-Mi1-Mi2-Hi	Sound Pressure Level (dBA) Lo-Mi1-Mi2-Hi	Starting Current (A) Outdoor	System Running Current (A) Heating / Cooling [MAX]	Phase	Mains Cable			Pipe Size mm(in)		Max Pipe Length (m)	Max Pipe Height (m)	Weight (kg) Indoor / Outdoor	Dimensions (mm) WxDxH Indoor / Outdoor	Fuse Rating (A) Indoor / Outdoor	
	Nominal Heating	Nominal Cooling	UK Heating	UK Cooling			Heating / Cooling (kW)									Indoor	Outdoor	Inter-connecting Cable	Gas	Liquid						
							Nominal	UK																		
R410A Wall Mounted Power Inverter Systems																										
PKA-RP35HAL PUHZ-ZRP35VKA		4.1 (1.6-5.2)	3.6 (1.6-4.5)	3.5 (1.35-4.4)	3.3 (1.45-4.15)	0.81	2.67	1.07 / 0.94	0.84 / 0.91	3.83 / 3.83	3.9 / 5.7	9-10.5-12	36-40-43	4.0	422 / 3.94 [13.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	13 / 43	898x249x295 / 800x300x630	6 / 16
PKA-RP50HAL PUHZ-ZRP50VKA		5.0 (2.5-7.3)	4.6 (2.3-5.6)	4.25 (2.15-6.2)	4.23 (2.1-5.15)	0.72	3.05	1.50 / 1.41	1.25 / 1.28	3.33 / 3.26	4.0 / 5.3	9-10.5-12	36-40-43	5.0	7.6 / 6.59 [13.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	13 / 46	898x249x295 / 800x300x630	6 / 16
PKA-RP60KAL PUHZ-ZRP60VHA		7.0 (2.8-8.2)	6.0 (2.7-6.7)	5.95 (2.4-6.95)	5.5 (2.5-6.15)	0.86	4.73	1.96 / 1.60	1.42 / 1.67	3.57 / 3.81	4.2 / 6.3	18-20-22	39-42-45	5.0	9.23 / 8.11 [19.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	21 / 67	1170x295x365 / 950x330x30x943	6 / 25
PKA-RP71KAL PUHZ-ZRP71VHA		8.0 (3.5-10.2)	7.1 (3.3-8.1)	6.8 (3.0-8.65)	6.55 (3.05-7.45)	0.78	5.11	2.19 / 1.80	1.60 / 1.86	3.65 / 3.94	4.3 / 6.5	18-20-22	39-42-45	6.0	8.75 / 7.79 [19.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	21 / 67	1170x295x365 / 950x330x30x943	6 / 25
PKA-RP100KAL PUHZ-ZRP100VKA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.73	6.72	3.04 / 2.65	2.36 / 2.58	3.68 / 3.77	4.0 / 6.1	20-23-26	41-45-49	12.0	11.46 / 11.44 [27.1]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	21 / 116	1170x295x365 / 1050x330x30x1338	6 / 32
PKA-RP100KAL PUHZ-ZRP100YKA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.73	6.72	3.04 / 2.65	2.36 / 2.58	3.68 / 3.77	4.0 / 6.0	20-23-26	41-45-49	4.0	4.82 / 4.41 [8.6]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	21 / 124	1170x295x365 / 1050x330x30x1338	6 / 16
R410A Wall Mounted Standard Inverter Systems																										
PKA-RP100KAL PUHZ-P100VHA4		11.2 (4.5-12.5)	9.4 (4.9-11.2)	9.5 (3.85-10.65)	8.65 (4.5-10.3)	0.75	6.49	3.49 / 3.12	3.11 / 2.65	3.21 / 3.01	3.8 / 4.8	20-23-26	41-45-49	12.0	15.20 / 14.55 [28.6]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	21 / 75	1170x295x365 / 950x330x30x943	6 / 32
PKA-RP100KAL PUHZ-P100YHA2		11.2 (4.5-12.5)	9.4 (4.9-11.2)	9.5 (3.85-10.65)	8.65 (4.5-10.3)	0.75	6.49	3.49 / 3.12	3.11 / 2.65	3.21 / 3.01	3.8 / 4.8	20-23-26	41-45-49	4.0	5.76 / 5.50 [13.6]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	21 / 77	1170x295x365 / 950x330x30x943	6 / 16
R410A Wall Mounted Zubadan Inverter Systems																										
PKA-RP100KAL PUHZ-SHWI12VHA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	11.1 (4.45-13.85)	9.2 (4.5-10.5)	0.73	6.72	3.10 / 2.92	2.76 / 2.49	3.61 / 3.42	3.8 / 5.2	20-23-26	41-45-49	14.0	11.78 / 11.67 [35.6]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	21 / 120	1170x295x365 / 950x330x30x1350	6 / 40
PKA-RP100KAL PUHZ-SHWI12YHA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	11.1 (4.45-13.85)	9.2 (4.5-10.5)	0.73	6.72	3.10 / 2.92	2.76 / 2.49	3.61 / 3.42	3.8 / 5.2	20-23-26	41-45-49	3.0	4.24 / 4.26 [13.6]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	21 / 134	1170x295x365 / 950x330x30x1350	6 / 16
R410A Ceiling Concealed Ducted Inverter Systems																										
SEZ-KD25VAQ SUZ-KA25VA3		2.9 (0.9-4.5)	2.5 (0.9-3.2)	2.5 (0.75-3.75)	2.4 (0.9-3.15)	0.80	1.92	0.84 / 0.75	0.68 / 0.67	3.46 / 3.33	3.5 / 5.2	6-7-9	22-25-29	3.58	3.90 / 3.39 [7.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	18 / 30	790x700x200 / 800x285x550	6 / 10
SEZ-KD35VAQ SUZ-KA35VA3		3.8 (0.9-5.0)	3.5 (1.0-3.9)	3.1 (0.75-4.15)	3.45 (1.0-3.85)	0.78	2.65	1.02 / 1.03	0.94 / 0.82	3.72 / 3.39	3.9 / 5.2	7-9-10	23-28-33	5.0	4.83 / 4.81 [8.7]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	21 / 35	990x700x200 / 800x285x550	6 / 10
SEZ-KD50VAQ SUZ-KA50VA3		6.4 (1.1-7.2)	5.1 (1.1-5.6)	5.3 (0.9-6.0)	5.05 (1.1-5.55)	0.78	3.94	1.81 / 1.64	1.49 / 1.45	3.54 / 3.11	3.9 / 5.2	10-13-15	29-33-36	7.57	7.31 / 7.05 [12.7]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	30	30	23 / 54	990x700x200 / 840x330x880	6 / 20
SEZ-KD60VAQ SUZ-KA60VA3		7.4 (0.9-8.0)	5.6 (1.1-6.3)	6.15 (0.75-6.65)	5.55 (1.1-6.25)	0.79	4.33	2.20 / 1.86	1.69 / 1.76	3.36 / 3.01	3.9 / 5.2	12-15-18	29-33-37	8.57	7.93 / 8.09 [14.7]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	6.35 (1/4")	30	30	27 / 50	1190x700x200 / 840x330x880	6 / 20
SEZ-KD71VAQ SUZ-KA71VA3		8.1 (0.9-10.4)	7.1 (0.9-8.3)	6.7 (0.75-8.65)	7.0 (0.9-8.25)	0.74	5.18	2.27 / 2.36	2.15 / 1.81	3.57 / 3.01	3.8 / 5.2	12-16-20	29-34-39	9.29	9.79 / 9.69 [17.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	27 / 53	1190x700x200 / 840x330x880	6 / 20
R410A Ceiling Concealed Ducted Power Inverter Systems																										
PEAD-RP35JAQ PUHZ-ZRP35VKA		4.1 (1.6-5.2)	3.6 (1.6-4.5)	3.5 (1.35-4.4)	3.3 (1.45-4.15)	0.85	2.81	0.95 / 0.89	0.79 / 0.81	4.32 / 4.04	4.0 / 5.6	10-12-14	23-27-30	4.0	4.45 / 4.18 [4.1]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	26 / 43	900x732x250 / 809x300x630	6 / 16
PEAD-RP50JAQ PUHZ-ZRP50VKA		6.0 (2.5-7.3)	5.0 (2.3-5.6)	5.1 (2.15-6.2)	4.6 (2.1-5.15)	0.84	3.86	1.50 / 1.44	1.28 / 1.28	4.00 / 3.47	4.3 / 5.5	12-14.5-17	26-31-35	5.0	7.65 / 7.09 [14.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	28 / 46	900x732x250 / 809x300x630	6 / 16
PEAD-RP60JAQ PUHZ-ZRP60VHA		7.0 (2.8-8.2)	6.1 (2.7-6.7)	5.95 (2.4-6.95)	5.5 (2.5-6.15)	0.83	4.57	1.79 / 1.65	1.47 / 1.52	3.91 / 3.70	4.1 / 5.8	14.5-18-21	25-29-33	5.0	9.76 / 8.68 [20.6]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	33 / 67	1100x732x250 / 950x330x30x943	6 / 25
PEAD-RP71JAQ PUHZ-ZRP71VHA		8.0 (3.5-10.2)	7.1 (3.3-8.1)	6.8 (3.0-8.65)	6.55 (3.05-7.45)	0.83	5.44	2.03 / 2.01	1.79 / 1.73	3.94 / 3.53	3.9 / 5.6	17.5-21-25	26-30-34	6.0	9.56 / 8.64 [21.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	33 / 67	1100x732x250 / 950x330x30x943	6 / 25
PEAD-RP100JAQ PUHZ-ZRP100VKA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.82	7.54	2.60 / 2.63	2.34 / 2.21	4.31 / 3.80	4.2 / 5.6	24-29-34	29-34-38	12.0	12.53 / 12.55 [29.2]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	41 / 116	1400x732x250 / 1050x330x30x1338	6 / 32
PEAD-RP125JAQ PUHZ-ZRP125VKA		14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.84	9.66	3.63 / 4.05	3.60 / 3.09	3.86 / 3.09	3.8 / 4.8	29.5-33.5-42	33-36-40	12.0	17.95 / 18.9 [29.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	43 / 116	1400x732x250 / 1050x330x30x1338	6 / 32
PEAD-RP140JAQ PUHZ-ZRP140VKA		16.0 (5.7-18.0)	13.4 (6.2-15.3)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.84	10.84	4.20 / 4.36	3.88 / 3.57	3.81 / 3.07	3.6 / 4.3	32-39-46	34-38-43	12.0	22.71 / 23.1 [30.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	47 / 119	1600x732x250 / 1050x330x30x1338	6 / 40
PEAD-RP100JAQ PUHZ-ZRP100YKA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.82	7.54	2.60 / 2.63	2.34 / 2.21	4.31 / 3.80	4.2 / 5.5	24-29-34	29-34-38	4.0	5.45 / 5.52 [											

Model Reference		Capacity (kW)				Nominal & UK SHF	UK Sensible Cooling (kW)	System Power Input Heating / Cooling (kW)		Nominal COP / EER (BSEN14511)	SCOP / SEER (BSEN14825)	Airflow (m³/min) Lo-Mi1-Mi2-Hi	Sound Pressure Level (dB) Lo-Mi1-Mi2-Hi	Starting Current (A) Outdoor	System Running Current (A) Heating / Cooling [MAX]	Phase	Mains Cable			Pipe Size mm(in)		Max Pipe Length (m)	Max Pipe Height (m)	Weight (kg) Indoor / Outdoor	Dimensions (mm) WxDxH Indoor / Outdoor		Fuse Rating (A) Indoor / Outdoor
		Nominal Heating	Nominal Cooling	UK Heating	UK Cooling			Nominal	UK								Indoor	Outdoor	Inter-connecting Cable	Gas	Liquid						
R410A Ceiling Cassette Power Inverter Systems																											
PLA-ZRP35BA PUHZ-ZRP35VKA		4.1 (1.6-5.2)	3.6 (1.6-4.5)	3.5 (1.35-4.4)	3.3 (1.45-4.15)	0.96	3.17	0.86 / 0.79	0.77 / 0.67	4.77 / 4.56	4.6 / 6.8	11-13-15-16	27-28-29-31	4.0	4.17 / 3.82 [13.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	23 / 43	840x840x258 / 809x300x23x630	6 / 16	
PLA-ZRP50BA PUHZ-ZRP50VKA		6.0 (2.5-7.3)	5.0 (2.3-5.6)	5.1 (2.15-6.2)	4.6 (2.1-5.15)	0.84	3.86	1.57 / 1.43	1.40 / 1.22	3.82 / 3.50	4.6 / 6.4	12-14-16-18	28-29-31-32	5.0	7.13 / 6.49 [13.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	23 / 46	840x840x258 / 809x300x23x630	6 / 16	
PLA-ZRP60BA PUHZ-ZRP60VHA		7.0 (2.8-8.2)	6.0 (2.7-6.7)	6.0 (2.38-6.97)	5.6 (2.48-5.98)	0.77	4.31	2.04 / 1.90	1.71 / 1.51	3.43 / 3.43	4.2 / 6.1	12-14-16-18	28-29-31-32	5.0	9.14 / 7.98 [19.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	23 / 67	840x840x298 / 950x330x30x943	6 / 25	
PLA-ZRP71BA PUHZ-ZRP71VHA		8.0 (3.5-10.2)	7.1 (3.3-8.1)	6.8 (3.0-8.65)	6.55 (3.1-7.45)	0.85	5.57	1.99 / 1.77	1.77 / 1.50	4.02 / 4.01	4.5 / 6.7	17-19-21-23	28-30-32-34	6.0	8.80 / 7.81 [19.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 / 67	840x840x298 / 950x330x30x943	6 / 25	
PLA-ZRP100BA PUHZ-ZRP100VKA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.74	6.81	2.61 / 2.60	2.32 / 2.21	4.29 / 3.85	4.6 / 6.5	20-23-26-30	32-34-37-40	12.0	11.9 / 11.9 [27.2]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	26 / 116	840x840x298 / 1050x330x30x1338	6 / 32	
PLA-ZRP125BA PUHZ-ZRP125VKA		14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.74	8.51	3.67 / 3.87	3.27 / 3.29	3.81 / 3.23	4.1 / 6.0	22-25-28-31	34-36-39-41	12.0	16.4 / 17.3 [27.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	27 / 116	840x840x298 / 1050x330x30x1338	6 / 32	
PLA-ZRP140BA PUHZ-ZRP140VKA		16.0 (5.7-18.0)	13.4 (6.2-15.0)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.72	9.29	4.70 / 4.37	4.18 / 3.71	3.40 / 3.07	4.5 / 6.1	24-26-29-32	36-39-42-44	12.0	21.1 / 19.8 [29.1]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	27 / 119	840x840x298 / 1050x330x30x1338	6 / 40	
PLA-ZRP100BA PUHZ-ZRP100YKA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.74	6.81	2.61 / 2.60	2.32 / 2.21	4.29 / 3.85	4.6 / 6.4	20-23-26-30	32-34-37-40	4.0	4.82 / 4.84 [8.7]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	26 / 124	840x840x298 / 1050x330x30x1338	6 / 16	
PLA-ZRP125BA PUHZ-ZRP125YKA		14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.74	8.51	3.67 / 3.87	3.27 / 3.29	3.81 / 3.23	4.1 / 5.9	22-25-28-31	34-36-39-41	4.0	6.25 / 6.64 [10.3]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	27 / 126	840x840x298 / 1050x330x30x1338	6 / 16	
PLA-ZRP140BA PUHZ-ZRP140YKA		16.0 (5.7-18.0)	13.4 (6.2-15.0)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.72	9.29	4.70 / 4.37	4.18 / 3.71	3.40 / 3.07	4.5 / 6.0	24-26-29-32	36-39-42-44	4.0	8.09 / 7.68 [12.1]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	27 / 132	840x840x298 / 1050x330x30x1338	6 / 16	
R410A Ceiling Cassette Standard Inverter Systems																											
PLA-RP35BA SUZ-KA35VA3		3.6 (0.9-5.0)	3.6 (1.0-3.9)	3.1 (0.75-4.15)	3.55 (1.0-3.85)	0.84	2.77	0.94 / 1.09	0.85 / 0.87	3.83 / 3.30	3.9 / 5.2	11-12-13-15	27-28-29-31	5.0	4.51 / 4.57 [8.42]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	22 / 35	840x840x258 / 800x285x550	6 / 10	
PLA-RP50BA SUZ-KA50VA3		6.0 (0.9-7.2)	5.5 (1.1-5.6)	5.0 (0.75-6.0)	5.45 (1.1-5.55)	0.81	4.41	1.75 / 1.71	1.59 / 1.37	3.43 / 3.22	3.9 / 5.2	12-14-16-18	28-29-31-32	7.57	6.97 / 6.78 [12.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	30	30	22 / 54	840x840x258 / 840x330x850	6 / 20	
PLA-RP60BA SUZ-KA60VA3		6.9 (0.9-8.0)	6.1 (1.1-6.3)	5.75 (0.75-6.65)	6.05 (1.1-6.25)	0.76	4.60	1.97 / 1.87	1.79 / 1.50	3.50 / 3.26	3.9 / 5.2	12-14-16-18	28-29-31-32	8.57	7.59 / 7.82 [14.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	6.35 (1/4")	30	30	23 / 50	840x840x258 / 840x330x850	6 / 20	
PLA-RP71BA SUZ-KA71VA3		8.0 (0.9-10.2)	7.1 (0.9-8.1)	6.65 (0.75-8.5)	7.05 (0.9-8.05)	0.73	5.15	2.25 / 2.10	2.04 / 1.68	3.65 / 3.38	3.9 / 5.2	14-16-18-21	28-30-32-34	9.29	9.38 / 9.36 [16.6]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	23 / 53	840x840x258 / 840x330x880	6 / 20	
PLA-RP100BA PUHZ-P100VHA4		11.2 (4.5-12.5)	9.4 (4.9-11.2)	9.5 (3.85-10.65)	8.65 (4.5-10.3)	0.74	6.40	3.28 / 3.12	2.92 / 2.65	3.41 / 3.01	3.8 / 5.2	20-23-26-30	32-34-37-40	12.0	15.6 / 14.9 [28.9]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 / 75	840x840x298 / 950x330x30x943	6 / 32	
PLA-RP125BA PUHZ-P125VHA3		14.0 (5.0-16.0)	12.3 (5.5-14.0)	11.9 (4.25-13.6)	11.3 (5.05-12.9)	0.71	8.02	4.11 / 4.09	3.66 / 3.48	3.41 / 3.01	3.7 / 3.6	22-25-28-31	34-36-39-41	15.0	17.7 / 18.4 [29.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 / 99	840x840x298 / 950x330x30x1350	6 / 32	
PLA-RP140BA PUHZ-P140VHA3		16.0 (5.0-18.0)	13.6 (5.5-15.0)	13.6 (4.25-15.3)	12.5 (5.05-13.8)	0.71	8.88	4.98 / 5.21	4.43 / 4.43	3.21 / 2.61	3.4 / 3.1	24-26-29-32	36-39-42-44	15.0	22.3 / 23.5 [30.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	27 / 99	840x840x298 / 950x330x30x1350	6 / 40	
PLA-RP100BA PUHZ-P100YHA2		11.2 (4.5-12.5)	9.4 (4.9-11.2)	9.5 (3.85-10.65)	8.65 (4.5-10.3)	0.74	6.40	3.28 / 3.12	2.92 / 2.65	3.41 / 3.01	3.8 / 5.2	20-23-26-30	32-34-37-40	4.0	6.13 / 5.94 [13.9]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 / 77	840x840x298 / 950x330x30x943	6 / 16	
PLA-RP125BA PUHZ-P125YHA		14.0 (5.0-16.0)	12.3 (5.5-14.0)	11.9 (4.25-13.6)	11.3 (5.05-12.9)	0.71	8.02	4.11 / 4.09	3.66 / 3.48	3.41 / 3.01	3.7 / 3.6	22-25-28-31	34-36-39-41	5.0	7.03 / 7.18 [14.0]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 / 101	840x840x298 / 950x330x30x1350	6 / 16	
PLA-RP140BA2 PUHZ-P140YHA		16.0 (5.0-18.0)	13.6 (5.5-15.0)	13.6 (4.25-15.3)	12.5 (5.05-13.8)	0.71	8.88	4.98 / 5.21	4.43 / 4.43	3.21 / 2.61	3.4 / 3.1	24-26-29-32	36-39-42-44	5.0	8.58 / 8.99 [14.0]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	27 / 101	840x840x298 / 950x330x30x1350	6 / 16	
R410A Ceiling Cassette Zubadan Inverter Systems																											
PLA-ZRP71BA PUHZ-SHW80VHA		8.0 (4.5-10.2)	7.1 (4.9-8.1)	6.8 (3.9-8.65)	6.55 (4.5-7.45)	0.85	5.57	2.05 / 1.86	1.82 / 1.58	3.91 / 3.81	3.7 / 5.1	17-19-21-23	28-30-34-36	14.0	9.35 / 8.54 [30.2]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	25 / 120	840x840x258 / 950x330x30x1350	6 / 32	
PLA-ZRP100BA PUHZ-SHW112VHA		11.2 (4.5-14.0)	10.0 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.74	6.81	2.68 / 2.79	2.37 / 2.37	4.20 / 3.59	4.0 /																