


Heating

Product Information

PUHZ-SW50-120VKA/VHA(-BS)

Ecodan Split Air Source Heat Pumps

Making a
World of
Difference



Designed to meet
the demands of
today's heating
needs



Certificate Number: MCS HP0002
Product Reference: PUHZ-SW50VKA, PUHZ-SW75VHA,
PUHZ-SW120VHA

Our range of Ecodan split air source heat pumps includes 5, 7.5 and 12kW sizes. Now with the ability to cascade up to six units of the same output Ecodan split systems offer a capacity range from 5 to 72kW. Designed to suit a wide number of applications, these models offer a viable solution for the varying requirements that domestic and small commercial applications demand.

Key Features

- Split unit allowing water connections to be made internally
- No need for gas supply, flues or ventilation
- Single phase power supply with a low starting current
- Low maintenance and quiet operation
- Operates with outside temperatures as low as -20°C
- Multiple unit connection
- Hybrid function for use with conventional boilers
- 2-zone energy efficient space heating control
- Energy monitoring as standard
- Coastal protection models available (-BS)

Application Examples

- The vast majority of UK homes
- Small Retail Outlets
- Dental / Doctor's Surgeries
- Public Sector / Commercial Buildings



Air Conditioning | Heating
Ventilation | Controls



ecodan[®]
Renewable Heating Technology

Heating

Product Information

PUHZ-SW50-120VKA/VHA(-BS) Ecodan Split Air Source Heat Pumps

Making a
World of
Difference

OUTDOOR UNIT		PUHZ-SW50VKA(-BS)	PUHZ-SW75VHA(-BS)	PUHZ-SW120VHA(-BS)
HEAT PUMP SPACE HEATER - 55°C	ErP Rating	A++	A++	A++
	η_s	125%	127%	125%
	SCOP	3.20	3.26	3.21
HEAT PUMP SPACE HEATER - 35°C	ErP Rating	A++	A++	A++
	η_s	163%	154%	162%
	SCOP	4.16	3.92	4.13
HEAT PUMP COMBINATION HEATER - Large Profile ¹	ErP Rating	A	A	A
	η_{wh}	98%	93%	99%
	Capacity (kW)	5.25	7.0	11.2
HEATING ² (A-3/W35)	Power Input (kW)	1.84	2.24	3.71
	COP	2.85	3.12	3.02
OPERATING AMBIENT TEMPERATURE (°C DB) ⁷		-15 ~ +35°C	-20 ~ +35°C	-20 ~ +35°C
SOUND PRESSURE LEVEL AT 1M (dBA) ^{3,4}		46	51	54
LOW NOISE MODE (dBA) ³		42	48	51
WATER DATA - Water connections made at indoor hydrobox				
DIMENSIONS (mm)	Flow Rate (l/min)	11.8	22.9	45.9
	Width	809+62 ⁵	950	950
	Depth	300	330+30 ⁵	330+30 ⁵
	Height	630	943	1350
WEIGHT (kg)		43	75	118
	REFRIGERANT			
ELECTRICAL DATA	Type	R410A	R410A	R410A
	Charge (kg) - 10m pipe length	1.4	3.2	4.6
	Pipe Size - Gas/Liquid (mm (in))	12.7 (1/2") / 6.35 (1/4")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")
	Connection Type	Flared	Flared	Flared
	Max Pipe Length (m)	40	40	75
	Min Pipe Length (m)	2	5	5
	Max Height Difference (m)	30	10	30
	Electrical Supply	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
	Phase	Single	Single	Single
	Nominal Running Current [MAX] (A)	3.8 [13]	8.1 [19]	17.5 [29.5]
	Fuse Rating - MCB Sizes (A) ⁶	16	25	40

¹ Combination with EHST20(D)(C)-MHCW Cylinders

² Under normal heating conditions at outdoor temp: -3°CDB / -4°CWB, outlet water temp 35°C, inlet water temp 30°C

³ Under normal heating conditions at outdoor temp: 7°CDB / 6°CWB, outlet water temp 35°C, inlet water temp 30°C as tested to BS EN14511

⁴ Sound power level of the PUHZ-SW50VKA is 62dBA, PUHZ-SW75VHA2 is 65.6dBA, PUHZ-SW120VHA is 68.8dBA, as tested to BS EN12102

⁵ Grille

⁶ MCB Sizes BS EN60898-2 & BS EN60947-2

⁷ Heating maximum ambient temperature -21°CDB, DHW Hot water maximum ambient temperature -35°CDB


⁸ Electrical cover

η_s is the seasonal space heating energy efficiency (SSHEE) η_{wh} is the water heating energy efficiency


DIMENSIONS

PUHZ-SW50VKA(-BS)

Upper View




Front View




PUHZ-SW75VHA(-BS)

Upper View




Front View




PUHZ-SW120VHA(-BS)

Upper View



Front View



Telephone: 01707 282880

email: heating@meuk.mee.com web: heating.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2015. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.



Printed on September 26th 2015 SAP No. 282527



www.greengateway.mitsubishielectric.co.uk

Mitsubishi Electric UK's commitment
to the environment

Follow us @meuk_ies
Follow us @green_gateway

Mitsubishi Electric
Living Environmental Systems UK

youtube.com/mitsubishielectric2