

R410A Mr Slim

Quick Reference Guide 2015



Model Reference	Capacity (kW)				Nominal & UK SHF	System Power Input Heating / Cooling (kW)		Nominal COP / EER (BSEN14511)	SCOP / SEER (BSEN14825)	Airflow (m³/min) Lo-Mi1-Mi2-Hi	Sound Pressure Level (dBA) Lo-Mi1-Mi2-Hi	Starting Current (A) Outdoor	System Running Current (A) Heating / Cooling [MAX]	Phase	Mains Cable			Pipe Size mm(in)		Max Pipe Length (m)	Max Pipe Height (m)	Weight (kg) Indoor / Outdoor	Dimensions (mm) WxDxH Indoor / Outdoor	Fuse Rating (A) Indoor / Outdoor
	Nominal Heating	Nominal Cooling	UK Heating	UK Cooling		Nominal									Indoor	Outdoor	Inter-connecting Cable	Gas	Liquid					
R410A Wall Mounted Power Inverter Systems																								
PKA-RP35HAL PUHZ-ZRP35VKA	4.1 (1.6-5.2)	3.6 (1.6-4.5)	3.5 (1.35-4.4)	3.3 (1.45-4.15)	0.81	1.07 / 0.94	0.84 / 0.91	3.83 / 3.83	3.9 / 5.7	150-175-200	36-40-43	4.0	4.22 / 3.94 [13.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	13 / 43	898x249x295 / 800x300x630	6 / 16
PKA-RP50HAL PUHZ-ZRP50VKA	5.0 (2.5-7.3)	4.6 (2.3-5.6)	4.25 (2.15-6.2)	4.23 (2.1-5.15)	0.72	1.50 / 1.41	1.25 / 1.28	3.33 / 3.26	4.0 / 5.3	150-175-200	36-40-43	5.0	7.16 / 6.59 [13.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	13 / 46	898x249x295 / 800x300x630	6 / 16
PKA-RP60KAL PUHZ-ZRP60VHA	7.0 (2.8-8.2)	6.1 (2.7-6.7)	5.95 (2.4-6.95)	5.5 (2.5-6.15)	0.86	1.96 / 1.60	1.42 / 1.67	3.57 / 3.81	4.2 / 6.3	300-333-367	39-42-45	5.0	9.23 / 8.11 [19.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	21 / 67	1170x295x365 / 950x330x30x943	6 / 25
PKA-RP71KAL PUHZ-ZRP71VHA	8.0 (3.5-10.2)	7.1 (3.3-8.1)	6.8 (3.0-8.65)	6.55 (3.05-7.45)	0.78	2.19 / 1.80	1.60 / 1.86	3.65 / 3.94	4.3 / 6.5	300-333-367	39-42-45	6.0	8.75 / 7.79 [19.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	21 / 67	1170x295x365 / 950x330x30x943	6 / 25
PKA-RP100KAL PUHZ-ZRP100VKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.73	3.04 / 2.65	2.43 / 2.28	3.68 / 3.96	4.1 / 6.1	333-383-433	41-45-49	12.0	11.35 / 11.26 [27.1]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	21 / 116	1170x295x365 / 1050x330x30x1338	6 / 32
PKA-RP100KAL PUHZ-ZRP100YKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.73	3.04 / 2.65	2.43 / 2.28	3.68 / 3.96	4.1 / 6.0	333-383-433	41-45-49	4.0	4.06 / 4.03 [8.6]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	21 / 123	1170x295x365 / 1050x330x30x1338	6 / 16
R410A Wall Mounted Standard Inverter Systems																								
PKA-RP100KAL PUHZ-P100VHA4	11.2 (4.5-12.5)	9.4 (4.9-11.2)	9.5 (3.85-10.65)	8.65 (4.5-10.3)	0.75	3.49 / 3.12	3.11 / 2.65	3.21 / 3.01	3.8 / 4.8	333-383-433	41-45-49	12.0	15.20 / 14.55 [28.6]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	21 / 75	1170x295x365 / 950x330x30x943	6 / 32
PKA-RP100KAL PUHZ-P100YHA2	11.2 (4.5-12.5)	9.4 (4.9-11.2)	9.5 (3.85-10.65)	8.65 (4.5-10.3)	0.75	3.49 / 3.12	3.11 / 2.65	3.21 / 3.01	3.8 / 4.8	333-383-433	41-45-49	4.0	5.76 / 5.50 [13.6]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	21 / 77	1170x295x365 / 950x330x30x943	6 / 16
R410A Wall Mounted Zubadan Inverter Systems																								
PKA-RP100KAL PUHZ-SHWI12VHA	11.2 (4.5-14.0)	10.0 (4.9-11.4)	11.1 (4.45-13.85)	9.2 (4.5-10.5)	0.73	3.10 / 2.92	2.76 / 2.49	3.61 / 3.42	3.8 / 5.2	333-383-433	41-45-49	14.0	11.78 / 11.67 [35.6]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	21 / 120	1170x295x365 / 950x330x30x1350	6 / 40
PKA-RP100KAL PUHZ-SHWI12YHA	11.2 (4.5-14.0)	10.0 (4.9-11.4)	11.1 (4.45-13.85)	9.2 (4.5-10.5)	0.73	3.10 / 2.92	2.76 / 2.49	3.61 / 3.42	3.8 / 5.2	333-383-433	41-45-49	3.0	4.24 / 4.26 [13.6]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	21 / 134	1170x295x365 / 950x330x30x1350	6 / 16
R410A Ceiling Concealed Ducted Power Inverter Systems																								
PEAD-RP35JAQ PUHZ-ZRP35VKA	4.1 (1.6-5.2)	3.6 (1.6-4.5)	3.5 (1.35-4.4)	3.3 (1.45-4.15)	0.85	0.95 / 0.89	0.79 / 0.81	4.32 / 4.04	4.0 / 5.6	167-200-233	23-27-30	4.0	4.45 / 4.18 [14.1]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	26 / 43	900x732x250 / 809x300x630	6 / 16
PEAD-RP50JAQ PUHZ-ZRP50VKA	6.0 (2.5-7.3)	5.0 (2.3-5.6)	5.1 (2.15-6.2)	4.6 (2.1-5.15)	0.84	1.50 / 1.44	1.28 / 1.28	4.00 / 3.47	4.3 / 5.5	200-242-283	26-31-35	5.0	7.65 / 7.09 [14.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	28 / 46	900x732x250 / 809x300x630	6 / 16
PEAD-RP60JAQ PUHZ-ZRP60VHA	7.0 (2.8-8.2)	6.1 (2.7-6.7)	5.95 (2.4-6.95)	5.5 (2.5-6.15)	0.83	1.79 / 1.65	1.47 / 1.52	3.91 / 3.70	4.1 / 5.8	242-300-350	25-29-33	5.0	9.76 / 8.68 [20.6]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	33 / 67	1100x732x250 / 950x330x30x943	6 / 25
PEAD-RP71JAQ PUHZ-ZRP71VHA	8.0 (3.5-10.2)	7.1 (3.3-8.1)	6.8 (3.0-8.65)	6.55 (3.05-7.45)	0.83	2.03 / 2.01	1.79 / 1.73	3.94 / 3.53	3.9 / 5.6	292-350-417	26-30-34	6.0	9.56 / 8.64 [21.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	33 / 67	1100x732x250 / 950x330x30x943	6 / 25
PEAD-RP100JAQ PUHZ-ZRP100VKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.82	2.60 / 2.63	2.08 / 2.26	4.31 / 3.91	4.2 / 5.6	400-483-567	29-34-38	12.0	12.53 / 12.55 [29.2]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	41 / 116	1400x732x250 / 1050x330x40x1338	6 / 32
PEAD-RP125JAQ PUHZ-ZRP125VKA	14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.84	3.86 / 4.05	3.1 / 3.48	3.99 / 3.24	3.9 / 5.0	492-558-700	33-36-40	12.0	17.95 / 18.9 [29.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	43 / 116	1400x732x250 / 1050x330x40x1338	6 / 32
PEAD-RP140JAQ PUHZ-ZRP140VKA	16.0 (5.7-18.0)	13.4 (6.2-15.3)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.84	3.81 / 4.36	3.04 / 3.74	3.93 / 3.1	4.0 / 4.8	533-650-767	34-38-43	12.0	22.7 / 21.3 [30.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	47 / 118	1600x732x250 / 1050x330x40x1338	6 / 40
PEAD-RP100JAQ PUHZ-ZRP100YKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.82	2.60 / 2.63	2.08 / 2.26	4.31 / 3.91	4.2 / 5.5	400-483-567	29-34-38	4.0	5.45 / 5.52 [10.7]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	41 / 123	1400x732x250 / 1050x330x40x1338	6 / 16
PEAD-RP125JAQ PUHZ-ZRP125YKA	14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.84	3.86 / 4.05	3.1 / 3.48	3.99 / 3.24	3.9 / 4.9	492-558-700	33-36-40	4.0	7.83 / 8.24 [12.3]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	43 / 125	1400x732x250 / 1050x330x40x1338	6 / 16
PEAD-RP140JAQ PUHZ-ZRP140YKA	16.0 (5.7-18.0)	13.4 (6.2-15.3)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.84	3.81 / 4.36	3.04 / 3.74	3.93 / 3.1	4.0 / 4.7	533-650-767	34-38-43	4.0	9.63 / 9.21 [13.8]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	47 / 131	1600x732x250 / 1050x330x40x1338	6 / 16
R410A Ceiling Concealed Ducted Inverter Systems																								
SEZ-KD25VAQ SUZ-KA25VA4	2.9 (1.3-4.5)	2.5 (1.5-3.2)	2.47 (1.11-3.83)	2.3 (1.38-2.94)	0.80	0.8 / 0.73	0.71 / 0.62	3.61 / 3.42	3.8 / 5.2	100-117-150	22-25-29	3.8	3.5 / 3.8 (7.4)	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	18 / 30	790x700x200 / 800x285x550	6 / 10
SEZ-KD35VAQ SUZ-KA35VA4	4.2 (1.7-5.0)	3.5 (1.4-3.9)	3.57 (1.45-4.25)	3.22 (1.29-3.59)	0.78	1.13 / 1.01	1.01 / 0.86	3.72 / 3.47	4.0 / 5.6	117-150-183	23-28-33	5.2	4.8 / 5.2 (8.7)	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	21 / 35	990x700x200 / 800x285x550	6 / 10
SEZ-KD50VAQ SUZ-KA50VA4	6.4 (1.7-7.2)	5.1 (2.3-5.6)	5.44 (1.45-6.12)	4.69 (2.12-5.15)	0.78	1.8 / 1.58	1.60 / 1.34	3.56 / 3.23	3.9 / 5.7	167-217-250	29-33-36	8.2	7.4 / 8.2 (12.7)	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	30	30	23 / 54	990x700x200 / 840x330x880	6 / 20
SEZ-KD60VAQ SUZ-KA60VA4	7.4 (2.5-8.0)	5.6 (2.3-6.3)	6.29 (2.13-6.8)	5.15 (2.12-5.8)	0.79	2.20 / 1.74	1.96 / 1.48	3.36 / 3.22	4.1 / 5.2	200-250-300	29-33-37	9.1	7.9 / 9.1 (14.7)	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	6.35 (1/4")	30	30	27 / 50	1190x700x200 / 840x330x880	6 / 20
SEZ-KD71VAQ SUZ-KA71VA4	8.1 (2.6-10.4)	7.1 (2.8-8.3)	6.89 (2.21-8.84)	6.53 (2.58-7.64)	0.74	2.27 / 2.21	2.02 / 1.88	3.57 / 3.21	3.8 / 5.2	200-267-333	29-34-39	10.5	10.5 / 9.7 (17.0)	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	27 / 53	1190x700x200 / 840x330x880	6 / 20
R410A Ceiling Concealed Ducted Standard Inverter Systems																								
PEAD-RP35JAQ SUZ-KA35VA4	4.1 (1.7-5.0)	3.6 (1.4-3.9)	3.49 (1.45-4.25)	3.31 (1.29-3.59)	0.85	1.11 / 1.50	0.99 / 1.28	3.69 / 3.42	4.0 / 5.5	167-200-233	23-27-30	5.1	4.90 / 5.1 [9.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	26 / 35	900x732x250 / 800x285x550	6 /

R410A Mr Slim Quick Reference Guide 2015



Model Reference	Capacity (kW)				Nominal & UK SHF	System Power Input Heating / Cooling (kW)		Nominal COP / EER (BSEN14511)	SCOP / SEER (BSEN14825)	Airflow (m³/min) Lo-Mi-L-Mi2-Hi	Sound Pressure Level (dBA) Lo-Mi-L-Mi2-Hi	Starting Current (A) Outdoor	System Running Current (A) Heating / Cooling [MAX]	Phase	Mains Cable			Pipe Size mm(in)		Max Pipe Length (m)	Max Pipe Height (m)	Weight (kg) Indoor / Outdoor	Dimensions (mm) WxDxH Indoor / Outdoor	Fuse Rating (A) Indoor / Outdoor	
	Nominal Heating	Nominal Cooling	UK Heating	UK Cooling		Nominal	UK								Indoor	Outdoor	Inter-connecting Cable	Gas	Liquid						
R410A Ceiling Cassette Power Inverter Systems																									
	PLA-ZRP35BA PUHZ-ZRP35VKA	4.1 (1.6-5.2)	3.6 (1.6-4.5)	3.5 (1.35-4.4)	3.3 (1.45-4.15)	0.96	0.86 / 0.79	0.77 / 0.67	4.77 / 4.56	4.6 / 6.8	183-217-250-267	27-28-29-31	4.0	4.17 / 3.82 [13]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	23 (6) / 43	840x840x258 / 809x300x23x630	6 / 16
	PLA-ZRP50BA PUHZ-ZRP50VKA	6.0 (2.5-7.3)	5.0 (2.3-5.6)	5.1 (2.15-6.2)	4.6 (2.1-5.15)	0.84	1.57 / 1.43	1.40 / 1.22	3.82 / 3.50	4.6 / 6.4	200-233-267-300	28-29-31-32	5.0	7.13 / 6.49 [13]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	23 (6) / 46	840x840x258 / 809x300x23x630	6 / 16
	PLA-ZRP60BA PUHZ-ZRP60VHA	7.0 (2.8-8.2)	6.1 (2.7-6.5)	6.0 (2.38-6.97)	5.6 (2.48-5.98)	0.77	2.04 / 1.90	1.71 / 1.51	3.43 / 3.43	4.2 / 6.1	200-233-267-300	28-29-31-32	5.0	9.14 / 7.98 [19]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	23 (6) / 67	840x840x298 / 950x330x30x943	6 / 25
	PLA-ZRP71BA PUHZ-ZRP71VHA	8.0 (3.5-10.2)	7.1 (3.3-8.1)	6.8 (3.0-8.65)	6.55 (3.1-7.45)	0.85	1.99 / 1.77	1.77 / 1.50	4.02 / 4.01	4.5 / 6.7	283-317-350-383	28-30-32-34	6.0	8.80 / 7.81 [19]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 (6) / 67	840x840x298 / 950x330x30x943	6 / 25
	PLA-ZRP100BA PUHZ-ZRP100VKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.74	2.60 / 2.16	2.24 / 2.09	4.31 / 4.4	4.8 / 6.9	333-383-433-500	32-34-37-40	12.0	11.92 / 11.93 [27]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	26 (6) / 116	840x840x298 / 1050x330x40x1338	6 / 32
	PLA-ZRP125BA PUHZ-ZRP125VKA	14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.74	3.67 / 3.87	3.27 / 3.29	3.81 / 3.23	4.7 / 6.4	367-417-467-517	34-36-39-41	12.0	16.37 / 17.3 [27]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	27 (6) / 116	840x840x298 / 1050x330x40x1338	6 / 32
	PLA-ZRP140BA PUHZ-ZRP140VKA	16.0 (5.7-18.0)	13.4 (6.2-15.0)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.72	4.70 / 4.37	4.18 / 3.71	3.40 / 3.07	4.5 / 6.1	400-433-483-533	36-39-42-44	12.0	21.41 / 19.75 [29]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	27 (6) / 118	840x840x298 / 1050x330x40x1338	6 / 40
	PLA-ZRP100BA PUHZ-ZRP100YKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.74	2.60 / 2.16	2.24 / 2.09	4.31 / 4.4	4.8 / 6.9	333-383-433-500	32-34-37-40	4.0	4.64 / 4.69 [8]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	26 (6) / 123	840x840x298 / 1050x330x40x1338	6 / 16
	PLA-ZRP125BA PUHZ-ZRP125YKA	14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.74	3.67 / 3.87	3.27 / 3.29	3.81 / 3.23	4.7 / 6.4	367-417-467-517	34-36-39-41	4.0	6.25 / 6.64 [10]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	27 (6) / 125	1840x840x298 / 1050x330x40x1338	6 / 16
	PLA-ZRP140BA PUHZ-ZRP140YKA	16.0 (5.7-18.0)	13.4 (6.2-15.0)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.72	4.70 / 4.37	4.18 / 3.71	3.40 / 3.07	4.5 / 6.0	400-433-483-533	36-39-42-44	4.0	8.09 / 7.68 [41]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	75	30	27 (6) / 131	840x840x298 / 1050x330x40x1338	6 / 16
R410A Ceiling Cassette Standard Inverter Systems																									
	PLA-RP35BA SUZ-KA35VA4	4.1 (1.7-5.0)	3.6 (1.4-3.9)	3.49 (1.45-4.25)	3.31 (1.29-3.59)	0.84	1.04 / 1.09	0.93 / 0.93	3.94 / 3.30	4.2 / 6.0	183-200-217-250	27-28-29-31	5.0	5.0 / 5.0 [8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	22 (6) / 35	840x840x258 / 800x285x550	6 / 10
	PLA-RP50BA SUZ-KA50VA4	6.0 (1.7-7.2)	5.5 (2.3-5.6)	5.1 (1.45-6.12)	5.06 (2.12-5.15)	0.81	1.75 / 1.66	1.56 / 1.41	3.43 / 3.31	4.0 / 6.0	200-233-267-300	28-29-31-32	7.7	7.7 / 7.4 [12]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	30	30	22 (6) / 54	840x840x258 / 840x330x880	6 / 20
	PLA-RP60BA SUZ-KA60VA4	6.9 (2.5-8.0)	6.1 (2.3-6.3)	5.87 (2.13-6.8)	5.61 (2.12-8.00)	0.76	1.97 / 1.84	1.75 / 1.56	3.50 / 3.32	4.1 / 6.0	200-233-267-300	28-29-31-32	8.7	7.9 / 8.7 [14]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	6.35 (1/4")	30	30	23 (6) / 50	840x840x258 / 840x330x880	6 / 20
	PLA-RP71BA SUZ-KA71VA4	8.0 (2.6-10.2)	7.1 (2.8-8.1)	6.8 (2.21-8.67)	6.53 (2.58-7.45)	0.73	2.25 / 2.10	2.0 / 1.79	3.50 / 3.38	4.3 / 5.8	233-267-300-350	28-30-32-34	9.7	9.2 / 9.7 [16]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	23 (6) / 53	840x840x258 / 840x330x880	6 / 20
	PLA-RP100BA PUHZ-PI00VHA4	11.2 (4.5-12.5)	9.4 (4.9-11.2)	9.5 (3.85-10.65)	8.65 (4.50-10.30)	0.74	3.28 / 3.12	2.92 / 2.65	3.41 / 3.01	3.8 / 5.2	333-383-433-500	32-34-37-40	12.0	15.57 / 14.92 [28]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 (6) / 75	840x840x298 / 950x330x30x943	6 / 32
	PLA-RP125BA PUHZ-PI25VHA3	14.0 (5.0-16.0)	12.3 (5.5-14.0)	11.9 (4.25-13.6)	11.3 (5.05-12.9)	0.71	4.11 / 4.09	3.66 / 3.48	3.41 / 3.01	3.7 / 3.6	367-417-467-517	34-36-39-41	15.0	17.68 / 18.37 [29]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 (6) / 99	840x840x298 / 950x330x30x1350	6 / 32
	PLA-RP140BA2 PUHZ-PI40VHA3	16.0 (5.0-18.0)	13.6 (5.5-15.0)	13.6 (4.25-15.3)	12.5 (5.05-13.8)	0.71	4.98 / 5.21	4.43 / 4.43	3.21 / 2.61	3.4 / 3.1	400-433-483-533	36-39-42-44	15.0	22.31 / 23.55 [30]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	27 (6) / 99	840x840x298 / 950x330x30x1350	6 / 40
	PLA-RP100BA PUHZ-PI00YHA2	11.2 (4.5-12.5)	9.4 (4.9-11.2)	9.5 (3.85-10.65)	8.65 (4.50-10.30)	0.74	3.28 / 3.12	2.92 / 2.65	3.41 / 3.01	3.8 / 5.2	333-383-433-500	32-34-37-40	4.0	6.13 / 5.94 [19]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 (6) / 77	840x840x298 / 950x330x30x943	6 / 16
	PLA-RP125BA PUHZ-PI25YHA	14.0 (5.0-16.0)	12.3 (5.5-14.0)	11.9 (4.25-13.6)	11.3 (5.05-12.9)	0.71	4.11 / 4.09	3.66 / 3.48	3.41 / 3.01	3.7 / 3.6	367-417-467-517	34-36-39-41	5.0	7.03 / 7.18 [40]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	25 (6) / 101	840x840x298 / 950x330x30x1350	6 / 16
	PLA-RP140BA2 PUHZ-PI40YHA	16.0 (5.0-18.0)	13.6 (5.5-15.0)	13.6 (4.25-15.3)	12.5 (5.05-13.8)	0.71	4.98 / 5.21	4.43 / 4.43	3.21 / 2.61	3.4 / 3.1	400-433-483-533	36-39-42-44	5.0	8.58 / 8.99 [40]	3	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	50	30	27 (6) / 101	840x840x298 / 950x330x30x1350	6 / 16
R410A Ceiling Cassette Inverter Systems																									
	PLA-SP71BA SUZ-SA71VA	8.0 (2.6-8.9)	7.1 (2.8-8.1)	6.8 (2.2-7.6)	6.5 (2.6-7.5)	0.73	2.25 / 2.10	2.00 / 1.79	3.21 / 3.21	3.8 / 5.6	233-267-300-350	28-30-32-34	9.7	9.38 / 9.36 [16]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	23 (6) / 53	840x840x258 / 840 x 330 x 880	6 / 20
	PLA-SP100BA PUHZ-SP100VHA	11.2 (4.5-11.5)	9.4 (4.9-9.9)	9.5 (3.8-9.8)	8.6 (4.5-9.1)	0.74	3.28 / 3.12	2.92 / 2.65	3.21 / 3.01	3.8 / 5.1	333-383-433-500	32-34-37-40	12.0	15.89 / 14.3 [28]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	25 (6) / 75	840x840x298 / 950 x 330 + 30 x 943	6 / 32
	PLA-SP125BA PUHZ-SP125VHA	13.5 (5.0-15.0)	12.3 (5.5-13.0)	11.5 (4.3-12.8-																					