



Changes for the Better

MITSUBISHI ELECTRIC CORPORATION
NAKATSUGAWA WORKS

1-3, Komaba-cho, Nakatsugawa City, Gifu Pref. 508-8666, JAPAN

EC DECLARATION OF CONFORMITY

Manufacturer : MITSUBISHI ELECTRIC CORPORATION, NAKATSUGAWA WORKS
Address : 1-3, Komaba-cho, Nakatsugawa City, Gifu Pref. 508-8666, JAPAN

Authorized representative : MITSUBISHI ELECTRIC EUROPE B. V.
Address : Harman House, 1 George Street, Uxbridge, Middlesex, UB8 1QQ, U. K.
(Kept technical documents)

Herewith declares that
Product name : Heat recovery unit
Trade mark : Lossnay
Series name : LGH
Model/Type : See Annex #0

-are in conformity with the provisions of the Low Voltage Directive 2006/95/EC, the Electromagnetic Compatibility Directive 2004/108/EC.

and furthermore declares that
- the following (parts/clauses of) harmonized standards have been applied:
. EN 60335-1:2002+A11:2004+A1:2004+A12:2006
. EN 60335-2-80:2003+A1:2004
. EN 61000-6-1:2007
. EN 61000-6-3:2007
. EN 62233:2003

Place : Japan

Date : 24 October 2011

MITSUBISHI ELECTRIC CORPORATION
Nakatsugawa Works

Name : Ryuzo Kuro
Position : Manager, Quality Control Section
Commercial & Industrial Ventilator Manufacturing Dept.



**MITSUBISHI
ELECTRIC**

Changes for the Better

MITSUBISHI ELECTRIC CORPORATION

NAKATSUGAWA WORKS

1-3, Komaba-cho, Nakatsugawa City, Gifu Pref. 508-8666, JAPAN

ANNEX #0: LIST OF MODEL NAMES

LGH-15RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 150m³/hr

LGH-25RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 250m³/hr

LGH-35RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 350m³/hr

LGH-50RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 500m³/hr

LGH-65RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 650m³/hr

LGH-80RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 800m³/hr

LGH-100RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 1000m³/hr

LGH-150RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 1500m³/hr

LGH-200RX5-E

Single (1) phase ~50Hz 220 – 240V
with design flow rate of 2000m³/hr