Product Information

Air Conditioning

PLA-ZM R410A Power Inverter Heat Pump (Three Phase)

4-Way Blow Ceiling Cassette System

Making a World of Difference

Mr.SLIM.



The PLA-ZM Power Inverter range is a ceiling cassette system that blends a host of outstanding features with a sophisticated streamlined design. Offering high seasonal efficiency, advanced control options and quiet operation, this range provides extreme flexibility and ease of installation.

Key Features

- Improved airflow control, including horizontal airflow for greater comfort
- Optional 3D i-see sensor grille (PLP-6EAE) provides customised comfort by automatically monitoring room occupancy, position and body temperatures
- Optional filter lowering operation down to 4m (PLP-6EAJ)
- Replace Technology available







Product Information

Air Conditioning

PLA-ZM R410A Power Inverter Heat Pump (Three Phase)

4-Way Blow Ceiling Cassette System

Making a World of Difference










| PLA-ZM - INDOOR UNITS | | PLA-ZM100EA | PLA-ZM125EA | PLA-ZM140EA | |
|------------------------|---------------------------------|----------------------------------|----------------------------------|----------------------------------|--|
| CAPACITY (kW) | Heating (nominal) | 11.2 (4.5-14.0) | 14.0 (5.0-16.0) | 16.0 (5.7-18.0) | |
| | Cooling (nominal) | 9.5 (4.9-11.4) | 12.5 (5.5-14.0) | 13.4 (6.2-15.0) | |
| | Heating (UK) | 9.5 (3.85-11.9) | 11.9 (4.25-13.6) | 13.6 (4.85-15.3) | |
| | Cooling (UK) | 9.2 (4.5-10.5) | 11.5 (5.05-12.9) | 12.9 (5.7-14.1) | |
| SHF (nominal) | | 0.75 | 0.67 | 0.67 | |
| COP / EER (nominal) | | 4.30 / 4.30 | 3.81 / 3.25 | 3.07 / 3.07 | |
| COP / SEER (BS EN | 14825) | 4.90 / 7.20 | 4.70 / 6.70 | 4.50 / 6.50 | |
| rP ENERGY EFFICIENCY (| CLASS Heating/Cooling | A++ / A++ | N/A | N/A | |
| IRFLOW (I/s) | Lo-Mi-Mi2-Hi | 317-367-417-467 | 350-400-433-483 | 400-433-483-533 | |
| PIPE SIZE mm (in) | Gas/Liquid | 15.88 (5/8") / 9.52 (3/8") | 15.88 (5/8") / 9.52 (3/8") | 15.88 (5/8") / 9.52 (3/8") | |
| OUND PRESSURE LEVEL (| dBA) Lo-Mi-Mi2-Hi | 31-34-37-40 | 33-36-39-41 | 36-39-42-44 | |
| OUND POWER LEVEL (dB | A) | 61 | 62 | 65 | |
| DIMENSIONS (mm) | Width x Depth x Height (Grille) | 840 (950) x 840 (950) x 298 (40) | 840 (950) x 840 (950) x 298 (40) | 840 (950) x 840 (950) x 298 (40) | |
| VEIGHT (kg) | Unit / Panel | 26 / 5 | 26 /5 | 26 / 5 | |
| LECTRICAL SUPPLY | • | Fed by Outdoor Unit | Fed by Outdoor Unit | Fed by Outdoor Unit | |
| USE RATING (BS88) - I | HRC (A) | 6 | 6 | 6 | |
| NTERCONNECTING (| CABLE No. Cores | 4 | 4 | 4 | |
| RILLE REFERENCE | | PLP-6EA | PLP-6EA | PLP-6EA | |
| VIRED REMOTE CON | ITROLLER REFERENCE | PAR-33MAA | PAR-33MAA | PAR-33MAA | |
| VIRELESS REMOTE (| CONTROLLER REFERENCE | PAR-SL100A-E | PAR-SL100A-E | PAR-SL100A-E | |
| | | <u> </u> | ব | | |


| WINELESS REIVIOTE CONTROLLER REFERENCE | PAN-SLIUUA-E | PAN-SLIUUA-E | PAN-SLIUUA-E | | |
|--|------------------------|------------------------|------------------------|--|--|
| PUHZ-ZRP - OUTDOOR UNITS | PUHZ-ZRP100YKA3 3 | PUHZ-ZRP125YKA3 3 | PUHZ-ZRP140YKA3 3 | | |
| SOUND PRESSURE LEVEL (dBA) Heating/Cooling | 51 / 49 | 52 / 50 | 52 / 50 | | |
| SOUND POWER LEVEL (dBA) Cooling | 69 | 70 | 70 | | |
| WEIGHT (kg) | 123 | 125 | 131 | | |
| DIMENSIONS (mm) Width x Depth x Height | 1050 x 330 + 40 x 1338 | 1050 x 330 + 40 x 1338 | 1050 x 330 + 40 x 1338 | | |
| ELECTRICAL SUPPLY | 380-415v,50Hz | 380-415v,50Hz | 380-415v,50Hz | | |
| PHASE | Three | Three | Three | | |
| SYSTEM POWER Heating/Cooling (nominal) | 2.60 / 2.20 | 3.67 / 3.84 | 4.84 / 4.56 | | |
| INPUT (kW) Heating/Cooling (UK) | 2.09 / 1.87 | 3.27 / 3.26 | 4.30 / 3.87 | | |
| STARTING CURRENT (A) | 4.0 | 4.0 | 4.0 | | |
| SYSTEM RUNNING CURRENT (A) Heating/Cooling [MAX] | 3.42 / 3.42 (8.0) | 5.92 / 5.96 (9.5) | 7.52 / 6.76 (13.0) | | |
| FUSE RATING (BS88) - HRC (A) | 16 | 16 | 16 | | |
| MAINS CABLE No. Cores | 5 | 5 | 5 | | |
| MAX PIPE LENGTH (m) | 75 | 75 | 75 | | |
| MAX HEIGHT DIFFERENCE (m) | 30 | 30 | 30 | | |
| CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R410A (GWP 2088) - 30m | 5.00 / 10.44 | 5.00 / 10.44 | 5.00 / 10.44 | | |
| MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R410A (GWP 2088) | 2.40 / 5.01 | 2.40 / 5.01 | 2.40 / 5.01 | | |

3 Three Phase


PRODUCT DIMENSIONS

PLA-ZM100/125/140EA





Front View



Side View

| O 1 | 628 | 00000 (F3)11 (CME) (RWN) | PE MECTON TO THE ATTACES DATE |
|-----------|-----|-----------------------------------|--|
| 0, [| | 6 | - B - B |
| S SHEDOND | Ť | 00/40 | 8 %o 8 |

| ZM | 0 | (2) | A | 8 | C | D |
|---------|---|--|-----|-----|------|------|
| 35/50 | REFRIGERANT PIPE & 6.35 FLARED CONNECTION 1/4F | REFRIGERANT PIPE 0 12.7 FLARED CONNECTION 10F | 241 | 258 | 76 | 76.5 |
| 60 | FLARED CONNECTION 3/8F | REFRIGERANT PIPE © 1588 FLARED CONNECTION SISF | | | 79.5 | 79.5 |
| 71 | REFRIGERANT PIPE © 9.52 | | 281 | 298 | | |
| 100-140 | | | | | | |



Telephone: 01707 282880 email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Malaysa. ØMitsubish lectric Europe 2017. Mitsubish and Mitsubish Electric are trademarks of Mitsubish Electric Europe B.V. The company reserves the right to make any variation to the equipment described, or to withdraw or replace products without prior notification or public amouncement. Mitsubish Electric is constantly developing and improving its products. All descriptions, illustratic drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand ramse may be trademarks or registered trademarks of their respective owners.

The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation tespecific conditions. Missuisini Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A, (MP-2088), R2C (MP-975), R407C (GWP-1774) or R154a (GWP-1403). These GWP are based on Pagicalation (EU) No ST/2014 from (PCC 414 edition. In case of Pagicalation (EU) No ST/2014 from (PCC 4144 (GWP-1014) (GWP-1014).











Mitsubishi Electric UK's commitment to the environment



Follow us @meuk_les Follow us @green_gateway



Mitsubishi Electric Living Environmental Systems UK



mitsubishielectric2



thehub.mitsubishielectric.co.uk