Product Information

Air Conditioning

Master BC Controllers CMB-P108/1012/1016V-JA/1016V-KA Making a World of Difference

CITYMULTI



At the heart of both the R2 and WR2 Series, the BC controller makes simultaneous heating and cooling possible. Improved system efficiency is achieved when energy is transferred intelligently around the building.

Key Features

- Allows unique 2-pipe heat recovery application
- Heating and cooling at the same time on larger systems
- Instructs the heat source unit/outdoor unit on the amount of refrigerant (liquid or gas) that is required to achieve the requested cooling or heating requirements
- Slim profile for more flexible installation
- Easy servicing and maintenance access through underside drain pan
- Brazed connections



Cooling | Heating | Ventilation | Controls

Product Information

Air Conditioning

Master BC Controllers CMB-P108/1012/1016V-JA/1016V-KA

Making a World of Difference









BC CONTROLLERS		CMB-P108V-JA	CMB-P1012V-JA	CMB-P1016V-JA	CMB-P1016V-KA
NUMBER OF CONNECTIONS		8	12	16	16
WEIGHT (kg)		45	55	63	65
DIMENSIONS (mm)	Width	911	1135	1135	1135
	Depth	639	639	639	639
	Height	246	246	246	246
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single
POWER INPUT (kW)		0.161	0.236	0.312	0.312
RUNNING CURRENT (A)		0.68	0.99	1.30	1.30
FUSE RATING (BS88) – HRC (A)		6	6	6	6
MAINS CABLE NO. CORES		3	3	3	3

Note: CMB-P-V-JA units are for use with PURY-P200-900Y(S)NW-A, PURY-EP200-900Y(S)NW-A & PQRY-P200-600Y(S)LM-A units only. CMB-P1016V-KA unit is for use with PURY-P950-1100YSNW-A & PURY-EP950-1100YSNW-A units only.


CMB-P108/1012/1016V-JA




Side View



CMB-P1016V-KA







Telephone: 01707 282880

email: air.conditioning@meuk.mee.com

web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland

Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Japan – Thailand – Malaysia. @Mitsubishi Electric Europe 2017. Mitsubishi and Misubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any varial ment described, or to withdraw or replace products without prior notification or public amouncement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrati publication present only general particulase and shall not from part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on reques as may be trademarks or registered trademarks of their respective owners. Country of origin: United Kingdom

ting is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electricial vielectrical engineer to select the correct cable size and fuse rating based on current regulation conditions. Mitsubishi Electrics air conditioning equipment and heat pump systems contain a fluorinated green/nuse gas, RATOA (GMP-2008), RAZ (GMP-6776), RATOA (GMP-1430), These GMP-1430). In Regulation (EQ) No 617/2014 from PCO4 the dation. In base of Regulation (EQ) No.6825(0111 from PCO4 dation, these are as tolows. RATOA (GMP-1776), RAZ (GMP-6776), RATOA (GMP-1730), In Regulation (EQ) No 617/2014 from PCO4 the dation. In base of Regulation (EQ) No.6825(0111 from PCO4 dation, No.617(02) from PCO4 from PCO4 the dation (EQ) No.6825(01111) from PCO4 dation.





www.greengateway.mitsubishielectric.co.uk

Mitsubishi Electric UK's commitment

to the environment

Green

Gateway