Product Information

Air Conditioning

R32 HVRF R2 Series High Efficiency (22.4-56kW) Simultaneous Heating and Cooling with Heat Recovery Outdoor Unit Making a World of Difference

CITY MULTI



Throughout the year, many buildings require cooling in some areas and heating in others - even in adjacent rooms. The outstanding City Multi R2 system meets these requirements by distributing surplus heat from cooling operations (and vice versa) to rooms where it is needed. This efficiency can result in energy savings up to 30% over conventional systems.

Key Features

- Highest specification, highest efficiency heat recovery system available
- Delivers the highest levels of comfort, both thermally and acoustically
- Flexible design, installation and maintenance







Product Information

R32 HVRF R2 Series High Efficiency (22.4-56kW) Simultaneous Heating and Cooling with **Heat Recovery Outdoor Unit**

Making a World of Difference










Air Conditioning


CADACITY (I-MA)	OUTDOOR UNITS		EM250YNW-A1	PURY- EM300YNW-A1	PURY-EM300YNW- A1 X 2HBC	PURY- EM350YNW-A1	PURY-EM350YNW- A1 X 2HBC	PURY- EM400YNW-A1	PURY- EM450YNW-A1	PURY- EM500YNW-A1
CAPACITY (kW)	Heating (nominal)	25.0	31.5	37.5	37.5	45.0	45.0	50.0	56.0	58.0
	Cooling (nominal)	22.4	28.0	33.5	33.5	40.0	40.0	45.0	50.0	56.0
	High Performance Heating (UK)	25.0	31.5	37.5	37.5	42.8	42.8	47.5	50.4	52.2
	COP Priority Heating (UK)	22.8	28.7	32.3	32.3	38.7	38.7	43.0	49.3	51.0
	Cooling (UK)	20.1	25.1	30.0	30.0	35.8	35.8	40.3	44.8	50.1
POWER INPUT (kW)	Heating (nominal)	6.23	8.84	10.46	9.93	13.10	12.16	13.88	15.77	17.45
	Cooling (nominal)	5.13	7.69	10.03	8.52	13.91	11.33	13.84	15.24	18.06
	High Performance Heating (UK)	7.54	10.70	14.33	13.60	17.95	16.66	16.10	18.29	20.24
	COP Priority Heating (UK)	6.23	8.84	10.46	9.93	13.10	12.16	13.46	15.30	16.93
	Cooling (UK)	2.98	4.46	5.82	4.94	8.07	6.57	9.00	9.91	11.74
COP / EER (nominal)		4.01 / 4.36	3.56 / 3.64	3.58 / 3.33	3.77 / 3.93	3.43 / 2.87	3.70 / 3.53	3.60 / 3.25	3.55 / 3.28	3.61 / 3.10
SCOP / SEER*		-	-	-	-	-	-	-	-	-
MAX No. OF CONNECTABLE INDOOR UNITS		30	37	45	45	35	35	40	45	50
MAX CONNECTABLE CAP	ACITY	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity	50~150% OU Capacity
AIRFLOW (m³/min)	High	170	185	240	240	250	250	315	315	295
PIPE SIZE mm (in)	Gas	19.05 (3/4")	22.2 (7/8")	22.2 (7/8")	22.2 (7/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")	28.58 (1-1/8")
	Liquid	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	19.05 (3/4")	19.05 (3/4")	19.05 (3/4")
SOUND PRESSURE LEVEL	L (dBA) Heating / Cooling	59.0 / 59.0	61.0 / 60.5	67.0 / 61.0	67.0 / 61.0	64.0 / 62.5	64.0 / 62.5	69.0 / 65.0	70.0 / 65.5	64.5 / 63.5
SOUND POWER LEVEL (d)	BA) Heating / Cooling	78.0 / 76.0	80.0 / 78.5	86.5 / 80.0	86.5 / 80.0	83.0 / 81.0	83.0 / 81.0	88.0 / 83.0	89.0 / 83.0	84.0 / 82.0
WEIGHT (kg)		231	231	231	231	276	276	280	305	348
DIMENSIONS (mm)	Width	920	920	920	920	1240	1240	1240	1240	1750
	Depth	740	740	740	740	740	740	740	740	740
(1798mm without legs)	Height	1858	1858	1858	1858	1858	1858	1858	1858	1858
ELECTRICAL SUPPLY'1		380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz
PHASE*1		Three	Three	Three	Three	Three	Three	Three	Three	Three
STARTING CURRENT (A)*1		8	8	8	8	8	8	8	8	8
NOMINAL SYSTEM RUNNING CURRENT (A)*1 Heating / Cooling [MAX]		9.9 / 8.2 [16.1]	14.1 / 12.3 [21.8]	16.7 / 16.0 [23.9]	15.9 / 13.6 [23.9]	21.0 / 22.3 [30.0]	19.5 / 18.1 [30.0]	22.2 / 22.1 [35.9]	25.2 / 24.4 [36.9]	27.9 / 28.9 [46.9]
GUARANTEED OPERATING RANGE (°C) Heating / Cooling		-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52	-20~15.5 / -5~52
FUSE RATING (MCB sizes BS EN 60947-2) - (A)*1		1 x 20	1 x 25	1 x 25	1 x 25	1 x 32	1 x 32	1 x 40	1 x 40	1 x 50
MAINS CABLE No. Cores*1		4	4	4	4	4	4	4	4	4
CHARGE REFRIGERANT (kg) / CO₂ EQUIVALENT (t) R32 (GWP 675)		5.2 / 3.5	5.2 / 3.5	5.2 / 3.5	5.2 / 3.5	8 / 5.4	8 / 5.4	8 / 5.4	10.8 / 7.3	10.8 / 7.3
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) R32 (GWP 675)		13.5 / 9.1	13.5 / 9.1	15.5 / 10.5	15.5 / 10.5	15.5 / 10.5	15.5 / 10.5	19.5 / 13.2	19.5 / 13.2	19.5 / 13.2

Notes: "SEER/SCOP available separately in the 'City Multi VRF Seasonal Efficiency' document. Based on Ecodesign Lot 21/6 to EN14825 standard. "1 A separate power supply is required for each module. Where more than one figure is quoted there are multiple modules. Specification subject to change. R410A equivalent systems are also available - please contact your local sales office for further information

PURY-EM200/250/300YNW-A1 Side View Front View




PURY-EM350/400/450YNW-A1




Upper View



PURY-EM500YNW-A1



Upper View





Telephone: 01707 282880 email: air.conditioning@meuk.mee.com web: airconditioning.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division

Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom – Japan – Thaland – Malaysia. (Mitsubish) Electric Europe 2019. Mitsubish) Electric are trademarks of Mitsubish Electric Europe B.V. The company reserves the right to make any variable technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubish Electric is constantly developing and improving its products. All descriptions illustrating and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand rames may be trademarks or registered trademarks of their respective owners.

The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation te specific conditions. Mitsubshi Electric's air conditioning equipment and hear pump systems contain a fluorinated greenhouse gas, R410A (GWP-2088), R32 (GWP-675), R407C (GWP-1774) or R134a (GWP-1430). These GWP are based on Regulation (EU) No 517/2014 from IPCC 4th edition. In case of Regulation (EU) No 628/2011 from IPCC 3rd edition, these are as tollows. R410A (GWP-1975), R32 (GWP-550), R407C (GWP-1650) or R134a (GWP-1300).



Mitsubishi Electric UK's commitment to the environment

Follow us @meuk_les Follow us @green_gateway

















