

Heating

Product Information

PUHZ-(H)W50 / PUHZ-W85/112VAA(-BS)
PUHZ-HW140VHA2(-BS)/YHA2(-BS)
Ecodan Monobloc Standalone
Air Source Heat Pumps

Making a
World of
Difference

ecodan



Designed
to meet the
demands of
today's heating
needs

Our range of Ecodan monobloc standalone air source heat pumps includes 5, 8.5, 11.2 and 14kW sizes. Now with the ability to cascade up to six units of the same output, Ecodan monobloc systems offer a capacity range from 5 through to 84kW.

Designed to suit a wide number of applications, these models offer a viable solution for the varying requirements that domestic and small commercial applications demand.

Key Features

- Self-contained unit, only requiring water and electric connections
- No need for gas supply, flues or ventilation
- Low maintenance and quiet operation
- Operates with outside temperatures as low as -25°C
- Optimised low ambient defrost control and operation
- Hybrid function, for use with conventional boilers
- Energy monitoring as standard



Cooling | Heating | Ventilation | Controls



ecodan®
Renewable Heating Technology

Heating

Product Information

PUHZ-(H)W50 / PUHZ-W85/112VAA(-BS)
PUHZ-HW140VHA2(-BS)/YHA2(-BS)
 Ecodan Monobloc Standalone
 Air Source Heat Pumps

Making a
World of
Difference

OUTDOOR UNIT		PUHZ-W50VHA2(-BS)	PUHZ-W85VAA(-BS)	PUHZ-W112VAA(-BS)	PUHZ-HW140VHA2(-BS)	PUHZ-HW140YHA2(-BS)
HEAT PUMP SPACE HEATER - 55°C	ErP Rating	A++	A++	A++	A++	A++
	$\eta_{s,e}$	127%	137%	133%	126%	126%
	SCOP	3.25	3.50	3.40	3.22	3.22
HEAT PUMP SPACE HEATER - 35°C	ErP Rating	A++	A++	A++	A++	A++
	$\eta_{s,e}$	162%	171%	170%	157%	157%
	SCOP	4.12	4.35	4.34	3.99	3.99
HEAT PUMP COMBINATION HEATER - Large Profile ¹	ErP Rating	A	A	A	A	A
	$\eta_{s,h}$	99%	104%	100%	96%	96%
HEATING ² (A-3/W35)	Capacity (kW)	4.8	8.3	11.0	14.0	14.0
	Power Input (kW)	1.63	2.86	3.73	4.81	4.81
	COP	2.95	2.90	2.95	2.91	2.91
OPERATING AMBIENT TEMPERATURE (°C DB)		-15 ~ +35°C	-20 ~ +35°C	-20 ~ +35°C	-25 ~ +35°C	-25 ~ +35°C
SOUND DATA	Pressure Level at 1m (dBA) ³	45	45	47	53	53
	Power Level (dBA) ⁴	61	58	60	65.5	67.5
WATER DATA	Pipework Size (mm)	22	28	28	28	28
	Flow Rate (l/min)	14.3	25.8	32.1	40.1	40.1
	Water Pressure Drop (kPa)	12	16.1	24.4	9	9
	DIMENSIONS (mm) ⁵	Width	950	1050	1050	1020
WEIGHT (kg)	Depth	330+30 ⁶	480	480	330+30 ⁶	330+30 ⁶
	Height	740	1020	1020	1350	1350
	ELECTRICAL DATA	Electrical Supply	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
REFRIGERANT CHARGE (kg) / CO ₂ EQUIVALENT (t)	Phase	Single	Single	Single	Single	3
	Nominal Running Current [MAX] (A)	5.4 [13]	9.1 [22.0]	10.9 [28.0]	14.9 [35]	5.1 [13]
	Fuse Rating - MCB Sizes (A) ⁷	16	25	32	40	16
	R410A (GWP 2088)	1.7 / 3.5	2.4/5.01	3.3/6.89	4.3 / 9.0	4.3 / 9.0

¹ Combination with EHPT20X-MHCW Cylinder
² Under normal heating conditions at outdoor temp: -3°CDB / -4°CWB, outlet water temp 35°C, inlet water temp 30°C.
³ Under normal heating conditions at outdoor temp: 7°CDB / 6°CWB, outlet water temp 35°C, inlet water temp 30°C as tested to BS EN14511.
⁴ Sound power level tested to BS EN12102.
⁵ 5 Grille. ⁶ Flow Temperature Controller (FTC) for standalone systems PAC-IF062B-E Dimensions WxDxH (mm) - 520x150x450 ⁷ MCB Sizes BS EN60898-2 & BS EN60947-2.
 $\eta_{s,e}$ is the seasonal space heating energy efficiency (SSHEE) $\eta_{s,h}$ is the water heating energy efficiency




Manufactured in the UK


DIMENSIONS

PUHZ-W50VHA2(-BS)

Upper View




Front View




PUHZ-W85 / 112VAA(-BS)

Upper View




Front View




PUHZ-(H)W140VHA2 / YHA2(-BS)

Upper View



Front View



Telephone: 01707 282880
 email: heating@meuk.mee.com
 web: les.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division
 Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881
 IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
 Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2018. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2088), R32 (GWP:675), R407C (GWP:1774) or R134a (GWP:1430). *These GWP values are based on Regulation (EU) No 517/2014 from IPCC 4th edition. In case of Regulation (EU) No.626/2011 from IPCC 3rd edition, these are as follows. R410A (GWP:1975), R32 (GWP: 550), R407C (GWP:1650) or R134a (GWP:1300).



www.greengateway.mitsubishielectric.co.uk
 Mitsubishi Electric UK's commitment to the environment

Follow us @meuk_Jes
 Follow us @green_gateway

Mitsubishi Electric
 Living Environmental Systems UK

mitsubishielectric2

thehub.mitsubishielectric.co.uk

Effective as of July 2018