

# R32 | Mr Slim Quick Reference Guide 2019

MODEL REFERENCE	Capacity (kW)				SHF (Nominal)	System Power Input Heating / Cooling (kW)		Nominal COP / EER	SCOP (nsh) / SEER (nsc) (BSEN14825)	Airflow (l/s) Heating / Cooling Lo-M1-M2-Hi	Sound Pressure Level (dBA) Heating / Cooling Lo-M1-M2-Hi	Starting Current (A) Outdoor	System Running Current (A) Heating / Cooling (MAX)	Phase	Mains Cable			Pipe Size mm (in)		Max Pipe Length (m)	Max Pipe Height (m)	Weight (kg)	Dimensions (mm) WxDxH Indoor / Outdoor	Fuse Rating (A) Indoor / Outdoor
	Nominal Heating	Nominal Cooling	UK Heating	UK Cooling		Nominal Heating	Nominal Cooling								Indoor	Outdoor	Inter-connecting Cable	Gas	Liquid					
<b>R32 PLA-ZM CEILING CASSETTE POWER INVERTER SYSTEMS</b>																								
PLA-ZM35EA PUZ-ZM35VKA	4.1 (1.6-5.2)	3.6 (1.6-4.5)	3.5 (1.35-4.4)	3.3 (1.45-4.15)	0.95	0.820 / 0.705	0.73 / 0.59	5.0 / 5.1	4.7 / 7.5	183-217-250-267	26-28-29-31	5.0	3.89 / 3.51 [13.2]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2)	6.35 (1/4)	50	30	21 (5) / 46	840x840x258 / 809x300x630	6 / 16
PLA-ZM50EA PUZ-ZM50VKA	6.0 (2.5-7.3)	5.0 (2.3-6.6)	5.1 (2.15-6.2)	4.6 (2.1-5.15)	0.85	1.363 / 1.106	1.21 / 0.94	4.4 / 4.52	4.9 / 7.6	200-233-267-300	27-29-31-32	5.0	6.05 / 5.00 [13.2]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2)	6.35 (1/4)	50	30	21 (5) / 46	840x840x258 / 809x300x630	6 / 16
PLA-ZM60EA PUZ-ZM60VKA	7.0 (2.8-8.2)	6.1 (2.7-6.5)	6.0 (2.38-6.97)	5.6 (2.48-5.98)	0.77	1.707 / 1.452	1.43 / 1.15	4.1 / 4.2	4.6 / 7.2	200-233-267-300	27-29-31-32	6.0	7.39 / 6.31 [19.2]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	55	30	21 (5) / 70	840x840x258 / 950x330x25x943	6 / 25
PLA-ZM71EA PUZ-ZM71VKA	8.0 (3.5-10.2)	7.1 (3.3-8.1)	6.8 (3.0-8.65)	6.55 (3.05-7.45)	0.72	1.818 / 1.651	1.61 / 1.39	4.4 / 4.3	4.8 / 7.6	283-317-350-383	28-30-33-36	6.0	7.79 / 7.06 [19.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	55	30	24 (5) / 70	840x840x298 / 950x330x25x943	6 / 25
PLA-ZM100EA PUZ-ZM100VKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.77	2.604 / 2.065	2.09 / 1.77	4.3 / 4.6	4.8 / 7.7	317-367-417-467	31-34-37-40	13.0	11.25 / 8.97 [27.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	100	30	26 (5) / 116	840x840x298 / 1050x330x40x1338	6 / 32
PLA-ZM125EA PUZ-ZM125VKA	14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.70	3.674 / 3.378	3.27 / 2.87	3.81 / 3.7	4.7 (185.1%) / 7.4 (303.3%)	350-400-433-483	33-36-39-41	13.0	15.77 / 14.53 [27.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	100	30	26 (5) / 116	840x840x298 / 1050x330x40x1338	6 / 32
PLA-ZM140EA PUZ-ZM140VKA	16.0 (5.7-18.0)	13.4 (6.2-15.0)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.70	4.312 / 3.772	3.83 / 3.15	3.71 / 3.55	4.6 (181.1%) / 7.0 (285.7%)	400-433-483-533	36-39-42-44	13.0	18.41 / 15.88 [28.7]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	100	30	26 (5) / 118	840x840x298 / 1050x330x40x1338	6 / 40
PLA-ZM100EA PUZ-ZM100YKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.77	2.604 / 2.065	2.09 / 1.77	4.3 / 4.6	4.8 / 7.5	317-367-417-467	31-34-37-40	6.0	3.75 / 2.96 [8.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	100	30	26 (5) / 123	840x840x298 / 1050x330x40x1338	6 / 16
PLA-ZM125EA PUZ-ZM125YKA	14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.70	3.674 / 3.378	3.27 / 2.87	3.81 / 3.7	4.7 (185.1%) / 7.0 (285.7%)	350-400-433-483	33-36-39-41	6.0	5.32 / 4.89 [10.0]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	100	30	26 (5) / 125	840x840x298 / 1050x330x40x1338	6 / 16
PLA-ZM140EA PUZ-ZM140YKA	16.0 (5.7-18.0)	13.4 (6.2-15.0)	13.6 (4.85-15.3)	12.9 (5.7-14.1)	0.70	4.312 / 3.772	3.83 / 3.15	3.71 / 3.55	4.6 (181.1%) / 6.9 (283.9%)	400-433-483-533	36-39-42-44	6.0	6.23 / 5.37 [13.7]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	100	30	26 (5) / 131	840x840x298 / 1050x330x40x1338	6 / 16
<b>R32 PLA-M CEILING CASSETTE STANDARD INVERTER SYSTEMS</b>																								
PLA-M35EA SUZ-M35VA	4.1 (1.0-5.0)	3.6 (0.8-3.9)	3.49 (0.85-4.26)	3.31 (0.74-3.6)	0.91	0.97 / 0.90	0.83 / 0.77	4.2 / 4.0	4.7 / 7.4	183-217-250-267	26-28-29-31	5.0	5.0 / 4.1 [8.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8)	6.35 (1/4)	20	12	19 (5) / 35	840x840x258 / 800x285x550	6 / 10
PLA-M50EA SUZ-M50VA	6.0 (1.5-7.2)	5.5 (1.2-7.2)	5.11 (1.28-6.13)	5.06 (1.10-5.15)	0.77	1.73 / 1.61	1.47 / 1.39	3.46 / 3.4	4.1 / 6.7	200-233-317-350	27-29-31-32	8.0	8.0 / 7.1 [13.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2)	6.35 (1/4)	30	30	19 (5) / 41	840x840x258 / 800x285x714	6 / 20
PLA-M60EA SUZ-M60VA	7.0 (1.6-8.0)	6.1 (1.6-6.3)	6.13 (1.36-6.81)	5.61 (1.47-5.8)	0.79	1.84 / 1.84	1.56 / 1.58	3.8 / 3.3	4.4 / 6.6	200-233-317-350	27-29-31-32	9.3	9.3 / 8.4 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	6.35 (1/4)	30	30	21 (5) / 54	840x840x258 / 840x330x880	6 / 20
PLA-M71EA SUZ-M71VA	8.0 (2.0-10.2)	7.1 (2.2-8.1)	6.81 (1.70-8.68)	6.53 (2.02-7.45)	0.74	2.21 / 1.91	1.88 / 1.64	3.61 / 3.7	4.5 / 7.5	233-283-317-350	28-30-32-34	9.5	9.5 / 9.1 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	30	30	21 (5) / 55	840x840x258 / 840x330x880	6 / 20
PLA-M100EA PUZ-M100VKA	11.2 (2.8-12.5)	9.5 (4.0-10.6)	9.63 (2.41-10.75)	8.65 (3.64-9.65)	0.77	3.01 / 2.71	2.71 / 2.50	3.71 / 3.5	4.6 / 7.0	317-383-433-483	31-34-37-40	13.0	13.0 / 11.7 [20]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	55	30	24 (5) / 76	840x840x298 / 1050x330x981	6 / 32
PLA-M125EA PUZ-M125VKA	13.5 (4.1-15.0)	12.1 (5.8-13.0)	11.49 (3.49-12.77)	11.01 (5.28-11.83)	0.72	3.63 / 4.01	3.27 / 3.33	3.71 / 3.01	4.1 (162%) / 5.2 (201.9%)	350-417-467-517	33-37-41-44	17.4	15.6 / 17.4 [26.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	65	30	26 (5) / 84	840x840x298 / 1050x330x981	6 / 32
PLA-M140EA PUZ-M140VKA	15.0 (4.2-15.8)	13.4 (5.8-14.1)	12.77 (3.57-13.45)	12.19 (5.28-12.83)	0.70	4.39 / 4.96	3.59 / 4.12	3.41 / 2.7	4.1 (161.3%) / 5.7 (227.2%)	400-433-483-533	36-39-42-44	21.5	19.0 / 21.5 [30]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	65	30	26 (5) / 84	840x840x298 / 1050x330x981	6 / 40
PLA-M100EA PUZ-M100YKA	11.2 (2.8-12.5)	9.5 (4.0-10.6)	9.63 (2.41-10.75)	8.65 (3.64-9.65)	0.77	3.01 / 2.71	2.71 / 2.50	3.71 / 3.5	4.6 / 7.0	317-383-433-483	31-34-37-40	4.7	4.7 / 4.2 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	55	30	24 (5) / 78	840x840x298 / 1050x330x981	6 / 16
PLA-M125EA PUZ-M125YKA	13.5 (4.1-15.0)	12.1 (5.8-13.0)	11.49 (3.49-12.77)	11.01 (5.28-11.83)	0.72	3.63 / 4.01	3.27 / 3.33	3.71 / 3.01	4.1 (162%) / 5.2 (201.9%)	350-417-467-517	33-37-41-44	6.3	5.6 / 6.3 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	65	30	26 (5) / 85	840x840x298 / 1050x330x981	6 / 16
PLA-M140EA PUZ-M140YKA	15.0 (4.2-15.8)	13.4 (5.8-14.1)	12.77 (3.57-13.45)	12.19 (5.28-12.83)	0.70	4.39 / 4.96	3.59 / 4.12	3.41 / 2.7	4.1 (161.3%) / 5.7 (227.2%)	400-433-483-533	36-39-42-44	7.8	6.9 / 7.8 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	65	30	26 (5) / 85	840x840x298 / 1050x330x981	6 / 16
<b>R32 PLA-SM CEILING CASSETTE INVERTER SYSTEMS</b>																								
PLA-SM71EA SUZ-SM71VA	8.0 (2.2-8.1)	7.1 (2.2-8.1)	6.80 (1.87-8.69)	6.53 (2.03-7.45)	0.75	2.28 / 1.97	1.94 / 1.70	3.5 / 3.6	3.9 / 6.0	233-283-317-350	28-30-32-34	9.7	9.7 / 8.3 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	30	30	21 (5) / 55	840x840x258 / 840x330x880	6 / 20
PLA-SM100EA PUZ-SM100VKA	11.2 (2.8-12.5)	9.5 (4.0-10.6)	9.63 (2.41-10.75)	8.55 (3.60-11.25)	0.77	3.10 / 2.79	2.64 / 2.40	3.61 / 3.4	4.5 / 6.0	317-383-433-483	31-34-37-40	13.4	13.4 / 12.1 [20]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	30	30	24 (5) / 76	840x840x298 / 1050x330x981	6 / 32
PLA-SM125EA PUZ-SM125VKA	13.5 (4.1-15.0)	12.1 (5.8-13.0)	11.61 (3.53-12.90)	10.89 (5.22-11.7)	0.73	3.73 / 4.17	3.17 / 3.59	3.61 / 2.9	3.9 (154.1%) / 5.5 (225.2%)	350-417-467-517	33-37-41-44	17.4	15.6 / 17.4 [26.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	40	30	26 (5) / 84	840x840x298 / 1050x330x981	6 / 32
PLA-SM140EA PUZ-SM140VKA	15.0 (4.2-15.8)	13.4 (5.8-14.1)	12.9 (3.61-13.59)	11.61 (5.22-12.69)	0.70	4.54 / 5.13	3.87 / 4.14	3.3 / 2.61	3.9 (153.3%) / 5.5 (224.9%)	400-433-483-533	36-39-42-44	22.3	19.0 / 22.3 [30]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8)	9.52 (3/8)	40	30	26 (5) / 84	840x840x298 / 1050x330x981	6 / 40
PLA-SM100EA PUZ-SM100YKA	11.2 (2.8-12.5)	9.5 (4.0-10.6)	9.63 (2.41-10.75)	8.55 (3.60-11.25)	0.77	3.10 / 2.79	2.64 / 2.40	3.61 / 3.4	4.5 / 6.0	317-383-433-483	31-34-37-40	4.8	4.8 / 4.3 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	30	30	24 (5) / 78	840x840x298 / 1050x330x981	6 / 16
PLA-SM125EA PUZ-SM125YKA	13.5 (4.1-15.0)	12.1 (5.8-13.0)	11.61 (3.53-12.9)	10.89 (5.22-11.7)	0.73	3.73 / 4.17	3.17 / 3.59	3.61 / 2.9	3.9 (154.1%) / 5.5 (225.2%)	350-417-467-517	33-37-41-44	6.3	5.6 / 6.3 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	40	30	26 (5) / 85	840x840x298 / 1050x330x981	6 / 16
PLA-SM140EA PUZ-SM140YKA	15.0 (4.2-15.8)	13.4 (5.8-14.1)	12.9 (3.61-13.59)	11.61 (5.22-12.69)	0.70	4.54 / 5.13	3.87 / 4.14	3.3 / 2.61	3.9 (153.3%) / 5.5 (224.9%)	400-433-483-533	36-39-42-44	8.1	6.9 / 8.1 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8)	9.52 (3/8)	40	30	26 (5) / 85	840x840x298 / 1050x330x981	6 / 16
<b>R32 SLZ-M 600x600 CEILING CASSETTE STANDARD INVERTER SYSTEMS</b>																								
SLZ-M15FA N/A - Multi-Split Only	1.7 (0.9-3.1)	1.5 (0.9-2.4)	-	-	-	-	-	-	-	100-108-117	24-26-28	-	-	Single	Fed by Outdoor Unit	-	4 Core	9.52 (3/8)	6.35 (1/4)	-	-	15 (3)	570x570x245	6
SLZ-M25FA SUZ-M25VA	3.2 (1.3-4.2)	2.5 (1.4-3.2)	2.72 (1.11-3.57)	2.30 (1.29-2.94)	0.78	0.88 / 0.65	0.75 / 0.56	3.61 / 3.8	4.3 / 6.3	108-125-142	24-26-28	3.7	3.7 / 3.0 [6.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8)	6.35 (1/4)	20	12	15 (3) / 30	570x570x245 / 800x285x550	6 / 10
SLZ-M35FA SUZ-M35VA	4.0 (1.0-5.0)	3.5 (0.7-3.9)	3.4 (0.85-4.25)	3.22 (0.64-3.59)	0.72	1.07 / 1.09	0.91 / 0.94	3.71 / 3.2	4.3 / 6.7	108-133-158	25-28-31	5.0	5.0 / 4.1 [8.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8)	6.35 (1/4)	20	12	15 (3) / 35	570x5	

MODEL REFERENCE	Capacity (kW)				S/F (Nominal)	System Power Input Heating / Cooling (kW)		Nominal COP / EER	SCOP (nsh) / SEER (nsc) (BSEN14825)	Airflow (l/s) Heating / Cooling Lo-M1-M2-Hi	Sound Pressure Level (dBA) Heating / Cooling Lo-M1-M2-Hi	Starting Current (A) Outdoor	System Running Current (A) Heating / Cooling [MAX]	Phase	Mains Cable			Pipe Size (mm)		Max Pipe Length (m)	Max Pipe Height (m)	Weight (kg)	Dimensions (mm) WxDxH Indoor / Outdoor	Fuse Rating (A) Indoor / Outdoor
	Nominal Heating	Nominal Cooling	UK Heating	UK Cooling		Nominal	UK								Gas	Liquid								
	Indoor		Inter-connecting Cable																					
<b>R32 PEAD-M CEILING CONCEALED DUCTED STANDARD INVERTER SYSTEMS</b>																								
PEAD-M35JA SUZ-M35VA	4.1 (1.1-5.0)	3.6 (0.8-3.9)	3.49 (0.94-4.25)	3.31 (0.74-3.59)	0.85	1.02 / 0.92	0.87 / 0.79	4.0 / 3.9	3.9 / 5.8	167-200-233	23-27-30	5.0	5.0 / 4.1 [8.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	26 / 35	900x732x250 / 800x285x550	6 / 10
PEAD-M50JA SUZ-M50VA	6.0 (1.5-7.2)	5.0 (1.7-5.6)	5.1 (1.28-6.12)	4.6 (1.56-5.15)	0.84	1.46 / 1.35	1.26 / 1.16	4.1 / 3.7	4.2 / 6.1	200-242-283	26-31-35	8.0	8.0 / 7.1 [13.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	30	30	27 / 41	900x732x250 / 800x285x550	6 / 20
PEAD-M60JA SUZ-M60VA	7.0 (1.6-8.0)	6.1 (1.6-6.3)	5.96 (1.36-6.8)	5.16 (1.47-5.8)	0.83	1.84 / 1.69	1.56 / 1.45	3.8 / 3.6	4.0 / 6.0	242-300-350	25-29-33	9.3	9.3 / 8.4 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	6.35 (1/4")	30	30	30 / 54	1100x732x250 / 840x330x880	6 / 20
PEAD-M71JA SUZ-M71VA	8.0 (2.0-10.2)	7.1 (2.2-8.1)	6.8 (1.7-8.67)	6.53 (2.02-7.45)	0.83	2.15 / 2.02	1.83 / 1.73	3.71 / 3.5	3.9 / 5.8	292-350-417	26-30-34	9.5	9.5 / 9.1 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	30 / 56	1100x732x250 / 840x330x880	6 / 20
PEAD-M100JA PUZ-M100VKA	11.2 (2.8-12.5)	9.5 (4.0-10.6)	9.63 (2.41-10.75)	8.65 (3.64-9.65)	0.82	2.94 / 2.87	2.65 / 2.38	3.8 / 3.3	4.0 / 5.4	400-483-567	29-34-38	12.0	12.0 / 11.6 [20.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	55	30	39 / 76	1400x732x250 / 1050x330x981	6 / 32
PEAD-M125JA PUZ-M125VKA	13.5 (4.1-15.0)	12.1 (6.0-13.0)	11.61 (3.53-12.9)	11.01 (5.46-11.83)	0.84	3.73 / 4.01	3.36 / 3.33	3.61 / 3.01	3.8 (152.7%) / 4.7 (192.6%)	492-592-700	33-36-40	16.2	15.0 / 16.2 [26.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	65	30	40 / 84	1400x732x250 / 1050x330x981	6 / 32
PEAD-M140JA PUZ-M140VKA	15.0 (4.2-15.8)	13.4 (6.1-14.1)	12.9 (3.61-13.59)	12.19 (5.55-12.83)	0.84	4.15 / 4.76	3.74 / 3.95	3.61 / 2.81	3.7 (145.4%) / 4.7 (192.6%)	533-650-767	34-38-43	19.3	16.8 / 19.3 [30.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	65	30	44 / 84	1600x732x250 / 1050x330x981	6 / 40
PEAD-M100JA PUZ-M100YKA	11.2 (2.8-12.5)	9.5 (4.0-10.6)	9.63 (2.41-10.75)	8.65 (3.64-9.65)	0.82	2.94 / 2.87	2.65 / 2.38	3.8 / 3.3	4.0 / 5.4	400-483-567	29-34-38	4.3	4.3 / 4.2 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	55	30	39 / 78	1400x732x250 / 1050x330x981	6 / 16
PEAD-M125JA PUZ-M125YKA	13.5 (4.1-15.0)	12.1 (6.0-13.0)	11.61 (3.53-12.9)	11.01 (5.46-11.83)	0.84	3.73 / 4.01	3.36 / 3.33	3.61 / 3.01	3.8 (152.7%) / 4.7 (192.6%)	492-592-700	33-36-40	5.8	5.4 / 5.8 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	65	30	40 / 85	1400x732x250 / 1050x330x981	6 / 16
PEAD-M140JA PUZ-M140YKA	15.0 (4.2-15.8)	13.4 (6.1-14.1)	12.9 (3.61-13.59)	12.19 (5.55-12.83)	0.84	4.15 / 4.76	3.74 / 3.95	3.61 / 2.81	3.7 (145.4%) / 4.7 (192.6%)	533-650-767	34-38-43	7.0	6.0 / 7.0 [11.5]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	65	30	44 / 85	1600x732x250 / 1050x330x981	6 / 16
<b>R32 SEZ-M CEILING CONCEALED DUCTED STANDARD INVERTER SYSTEMS</b>																								
SEZ-M25DA SUZ-M25VA	2.9 (1.3-4.2)	2.5 (1.4-3.2)	2.47 (1.11-3.57)	2.3 (1.29-2.94)	0.78	0.80 / 0.71	0.68 / 0.61	3.61 / 3.5	3.8 / 5.3	100-117-150	22-25-29	3.7	3.7 / 3.0 [6.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	18 / 30	790 x700x200 / 800x285x550	6 / 10
SEZ-M35DA SUZ-M35VA	4.2 (1.1-5.0)	3.5 (0.7-3.9)	3.57 (0.94-4.25)	3.22 (0.64-3.59)	0.76	1.07 / 1.00	0.91 / 0.86	3.9 / 3.5	4.1 / 5.9	117-150-183	23-28-33	5.0	5.0 / 4.1 [8.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	9.52 (3/8")	6.35 (1/4")	20	12	21 / 35	990x700x200 / 800x285x550	6 / 10
SEZ-M50DA SUZ-M50VA	6.0 (1.5-7.2)	5.0 (1.1-5.6)	5.1 (1.28-6.12)	4.6 (1.01-5.15)	0.76	1.61 / 1.54	1.37 / 1.32	3.71 / 3.23	4.0 / 6.0	167-217-250	29-33-36	8.0	8.0 / 7.1 [13.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	30	30	23 / 41	990x700x200 / 800x285x550	6 / 20
SEZ-M60DA SUZ-M60VA	7.4 (1.6-8.0)	6.1 (1.6-6.3)	6.29 (1.36-6.8)	5.61 (1.47-5.8)	0.79	2.04 / 1.84	1.73 / 1.58	3.61 / 3.3	4.2 / 5.5	200-250-300	29-33-37	9.3	9.3 / 8.4 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	6.35 (1/4")	30	30	27 / 54	1190x700x200 / 840x330x880	6 / 20
SEZ-M71DA SUZ-M71VA	8.0 (2.0-10.2)	7.1 (2.2-8.1)	6.8 (1.70-8.67)	6.53 (2.02-7.45)	0.74	2.28 / 2.15	1.94 / 1.85	3.5 / 3.3	3.9 / 5.5	200-267-333	29-34-39	9.5	9.5 / 9.1 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	27 / 55	1190x700x200 / 840x330x880	6 / 20
<b>R32 PCA-M CEILING SUSPENDED POWER INVERTER SYSTEMS</b>																								
PCA-M50KA PUZ-M50VKA	5.5 (2.5-6.6)	5.0 (2.3-5.6)	4.7 (2.15-5.6)	4.6 (2.1-5.15)	0.79	1.361 / 1.25	1.21 / 1.06	4.04 / 4.0	4.2 / 6.7	167-183-217-250	32-34-37-40	5.0	5.95 / 5.37 [13.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	50	30	26 / 46	960x680x230 / 800x330x630	6 / 16
PCA-M60KA PUZ-M60VHA	7.0 (2.8-8.2)	6.1 (2.7-6.7)	5.95 (2.4-6.95)	5.5 (2.5-6.15)	0.81	1.745 / 1.521	1.55 / 1.29	4.01 / 4.01	4.1 / 6.5	250-267-283-317	33-35-37-40	6.0	7.43 / 6.48 [19.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	55	30	32 / 70	1280x680x230 / 950x330x25x943	6 / 25
PCA-M71KA PUZ-M71VHA	8.0 (3.5-10.2)	7.1 (3.3-8.1)	6.8 (3.0-8.65)	6.55 (3.05-7.45)	0.76	2.156 / 1.829	1.92 / 1.55	3.71 / 3.88	4.2 / 6.7	267-283-300-333	35-37-39-41	6.0	9.23 / 7.81 [19.4]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	55	30	32 / 70	1280x680x230 / 950x330x25x943	6 / 25
PCA-M100KA PUZ-M100VKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.77	3.018 / 2.317	2.41 / 1.99	3.71 / 4.1	4.3 / 6.4	367-400-433-467	37-39-41-43	13.0	12.97 / 9.97 [27.2]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	100	30	37 / 116	1600x680x230 / 1050x330x40x1338	6 / 32
PCA-M125KA PUZ-M125VKA	14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.72	3.954 / 3.846	3.51 / 3.26	3.54 / 3.25	4.3 (168.8%) / 6.2 (249.5%)	383-417-450-483	39-41-43-45	13.0	16.87 / 16.46 [27.3]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	100	30	38 / 116	1600x680x230 / 1050x330x40x1338	6 / 32
PCA-M140KA PUZ-M140VKA	16.0 (5.7-18.0)	13.4 (6.2-15.0)	13.6 (4.85-15.3)	12.9 (5.7-13.8)	0.72	4.432 / 3.941	3.94 / 3.35	3.61 / 3.4	4.4 (173.5%) / 6.2 (249.5%)	400-433-483-533	41-43-45-48	13.0	18.76 / 16.66 [28.9]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	100	30	40 / 118	1600x680x230 / 1050x330x40x1338	6 / 40
PCA-M100KA PUZ-M100YKA	11.2 (4.5-14.0)	9.5 (4.9-11.4)	9.5 (3.85-11.9)	9.2 (4.5-10.5)	0.77	3.018 / 2.317	2.41 / 1.99	3.71 / 4.1	4.3 / 6.3	367-400-433-467	37-39-41-43	6.0	4.34 / 3.31 [8.7]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	100	30	37 / 123	1600x680x230 / 1050x330x40x1338	6 / 16
PCA-M125KA PUZ-M125YKA	14.0 (5.0-16.0)	12.5 (5.5-14.0)	11.9 (4.25-13.6)	11.5 (5.05-12.9)	0.72	3.954 / 3.846	3.51 / 3.26	3.54 / 3.25	4.3 (168.8%) / 6.1 (249.5%)	383-417-450-483	39-41-43-45	6.0	5.69 / 5.54 [10.3]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	100	30	38 / 125	1600x680x230 / 1050x330x40x1338	6 / 16
PCA-M140KA PUZ-M140YKA	16.0 (5.7-18.0)	13.4 (6.2-15.0)	13.6 (4.85-15.3)	12.9 (5.7-13.8)	0.72	4.432 / 3.941	3.94 / 3.35	3.61 / 3.4	4.4 (173.5%) / 6.1 (249.5%)	400-433-483-533	41-43-45-48	6.0	6.42 / 5.71 [13.9]	Three	Fed by Outdoor Unit	5 Core 380-415v	4 Core	15.88 (5/8")	9.52 (3/8")	100	30	40 / 131	1600x680x230 / 1050x330x40x1338	6 / 16
<b>R32 PCA-M CEILING SUSPENDED STANDARD INVERTER SYSTEMS</b>																								
PCA-M50KA SUZ-M50VA	6.0 (1.5-7.2)	5.0 (1.5-5.6)	5.1 (1.28-6.12)	4.6 (1.38-5.15)	0.79	1.61 / 1.51	1.37 / 1.30	3.71 / 3.3	4.1 / 6.0	167-183-217-250	32-34-37-40	8.0	8.0 / 7.1 [13.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	12.7 (1/2")	6.35 (1/4")	30	30	26 / 41	960x680x230 / 800x285x714	6 / 20
PCA-M60KA SUZ-M60VA	7.0 (1.6-8.0)	6.1 (1.6-6.3)	5.95 (1.36-6.8)	5.61 (1.47-5.8)	0.81	1.75 / 1.64	1.49 / 1.41	4.0 / 3.7	4.1 / 6.4	250-267-283-317	33-35-37-40	9.3	9.3 / 8.4 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	6.35 (1/4")	30	30	32 / 54	1280x680x230 / 840x330x880	6 / 20
PCA-M71KA SUZ-M71VA	8.0 (2.0-10.2)	7.1 (2.2-8.1)	6.8 (1.70-8.67)	6.53 (1.56-7.45)	0.76	2.21 / 1.97	1.88 / 1.69	3.61 / 3.6	4.1 / 6.5	267-283-300-333	35-37-39-41	9.5	9.5 / 9.1 [14.8]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	30	30	32 / 55	1280x680x230 / 840x330x880	6 / 20
PCA-M100KA PUZ-M100VKA	11.2 (2.8-12.5)	9.5 (4.0-10.6)	9.63 (2.41-10.75)	8.65 (3.64-9.65)	0.77	3.28 / 2.94	2.95 / 2.44	3.41 / 3.23	4.1 / 6.0	367-400-433-467	37-39-41-43	14.2	14.2 / 12.6 [20.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	55	30	37 / 76	1600x680x230 / 1050x330x981	6 / 32
PCA-M125KA PUZ-M125VKA	13.5 (4.1-15.0)	12.1 (5.7-13.0)	11.61 (3.53-12.9)	11.01 (5.19-11.83)	0.72	3.95 / 4.01	3.56 / 3.33	3.41 / 3.01	4.1 (162.7%) / 5.2 (213%)	383-417-450-483	39-41-43-45	17.3	17.0 / 17.3 [26.5]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	65	30	38 / 84	1600x680x230 / 1050x330x981	6 / 32
PCA-M140KA PUZ-M140VKA	15.0 (4.2-15.8)	13.4 (5.7-14.1)	12.9 (3.61-13.59)	12.19 (5.19-12.83)	0.72	4.28 / 5.36	3.85 / 4.45	3.5 / 2.5	4.0 (158.7%) / 5.1 (208%)	400-433-483-533	41-43-45-48	23.2	18.4 / 23.2 [30.0]	Single	Fed by Outdoor Unit	3 Core 220-240v	4 Core	15.88 (5/8")	9.52 (3/8")	65	30	40 / 84	1600x680x230 / 1050x330x981	6 / 40
PCA-M100KA PUZ-M100YKA	11.2 (2.8-12.5)	9.5 (4.0-10.6)	9.63 (2.41-10.75)	8.65 (3.64-9.65)</																				