



VERSATILE RANGE OF COMPACT, STYLISH **WALL MOUNTED AIR CONDITIONING SYSTEMS**





FROM 1.5 - 7.1kW



FOR COOLING OR HEATING SMALL TO MEDIUM SIZED SPACES **RETAIL UNITS • SMALL OFFICES**

CHOICE OF 5 SYSTEMS, PERFECT







REPLACE TECHNOLOGY, ALLOWING THE UPGRADE OF SYSTEMS UTILISING **EXISTING PIPING**

INCORPORATES

CAN BE CONTROLLED AND MONITORED

VIA SMARTPHONE, TABLET OR PC USING THE MELCloud APP



WALL MOUNTED SYSTEM **DESIGNER WALL**

M SERIES MSZ-LN R32



AVAILABLE FROM 1.8 - 6.1kW

MOUNTED SYSTEM



SYSTEM



RUBY RED ONYX BLACK PFARI WHITE NATURAL WHITE

DEEP, RICH COLOURS:

3D i-SEE SENSOR PROVIDES CUSTOMISED COMFORT

AVAILABLE IN A RANGE OF



PLASMA QUAD

USES POWERFUL PLASMA

TECHNOLOGY TO FILTER OUT

EVEN MICROSCOPIC PARTICLES

PLUS FILTER



ROOM OCCUPANCY, POSITION AND BODY TEMPERATURE

BY AUTOMATICALLY MONITORING

DUAL-BARRIER COATING TO HEAT EXCHANGER, FAN AND AIR DUCT PREVENTS DUST AND GREASE ACCUMULATION



AND MONITORING VIA THE MELCloud APP

BUILT-IN WI-FI INTERFACE

ENABLING CONTROL

BLENDS ENERGY EFFICIENCY WITH A SOPHISTICATED,

M SERIES MSZ-EF R32

ZEN WALL MOUNTED SYSTEM



OPERATION

STREAMLINED DESIGN **AVAILABLE FROM 2.5 - 5kW IMPRESSIVELY LOW POWER**



DISTINCTIVELY STYLED FRONT PANEL MAKES UNIT EASY TO

PERFORMANCE

WITH A POWERFUL



CONSUMPTION

UNIVERSAL CONTROLLER



CLEAN AND MAINTAIN



• SILVER

WHITE



MID-RANGE WALL MOUNTED SYSTEM

COMBINES ENERGY EFFICIENCY

WITH MODERN, COMPACT, STYLISH WHITE DESIGN **AVAILABLE FROM 1.5 - 7.1kW**

WALL MOUNTED SYSTEM





AS 19dBA

NOISE





M SERIES MSZ-HR R32

THE ROOM



INVERTER TECHNOLOGY

AVAILABLE FROM 2.5 - 5kW

CLASSIC WALL MOUNTED SYSTEM COST-EFFECTIVE FLAT PANEL WALL

ECONOMICAL AIR EXTREMELY CONDITIONING QUIET WITH IMPROVED **SOUND LEVELS** SCOP / SEER FIGURES



M SERIES MSY-TP HIGH SHF

WEEKLY TIMER

PROVIDES GREATER

CONTROL OF

SCHEDULING

WALL MOUNTED SYSTEM **INNOVATIVE HIGH SHF**

OPTIONAL

MELCloud

INTERFACE



COOLING ONLY UNIT WITH A HIGH SENSIBLE COOLING CAPACITY

REDUCES



WALL MOUNTED SYSTEM

AVAILABLE IN 3.5 AND 5kW

SHF'S UP TO 0.98 PERFECT FOR SMALL-SCALE IT COOLING APPLICATIONS

COOLING DOWN

TO -25°C OUTDOOR

AIR TEMPERATURE







R32 R410A 50%







