

# PCFY-P63VKM-ER1

## CIBSE TM65 Embodied Carbon Mid-level Calculation

**Assesment Date:** 

30th March 2023

Assessor / Organisation:

RI / Mitsubishi Electric LES UK

Contact:

embodied.carbon@meuk.mee.com

## Embodied Carbon with 'Mid-level TM65 Calculation' Method (kg CO<sub>2</sub>e) Total:

326

Embodied (	Carbon Resul	t per kW (kg	CO <sub>2</sub> e/kW):	Capa	acities (kW)*		7.1 46	
	 	 		 	 		Embodied Carbon -	
	326						Without Refrigerant Leakage (kg CO₂e)  Embodied Carbon - Refrigerant Leakage Only (kg CO₂e)	
-	50	100	150	200	250	300	kg CO <sub>2</sub> e	

#### PCFY-P63VKM-ER1 - Product Information

Type of product	VRF Indoor Unit
Capacity of equipment (kW)*	7.1
Product weight (kg)	32
Material breakdown for at least 95% of the product weight? (Y/N)	Υ
Service life of the product (years)	15
Type of refrigerant	R410A
Refrigerant GWP	2088
Energy consumption of the factory per unit of product (kWh)	14.67
Location of manufacture	Japan
Product Complexity	Category 3: High



<sup>\*</sup>Nominal cooling capacity conditions as per data book



## PCFY-P63VKM-ER1

#### CIBSE TM65 Embodied Carbon Mid-level Calculation

Embodied Carbon Results Breakdown (kg CO₂e)	
A1: Material extraction	160
A2: Transport	25
A3: Manufacturing	30
A4: Transport to Site	8
B1: Use	-
B3: Repair	23
C1: Deconstruction	-
C2: Transport	0
C3: Waste Processing	4
C4: Disposal	0

Lilibodied Carbon Results - Without Refrigerant Leakage (kg CO2e)	
A1-C4 (excluding B1,C1)	250
A1-C4 with Buffer Factor (excluding B1, C1)	326

#### Embodied Carbon Result - Refrigerant Leakage Only (kg CO2e)

B1 (Refrigerant leakage during use) + C1 (Refrigerant leakage end of life)

Embodied Carbon Pocults - without Pofridorant Loakada (kd CO a)

Assumptions		
A1: Material carbon coefficient source	TM65 Table 2.1 & The ICE Database	
B1: Refrigerant annual leakage rate (%)	2	
C1: Refrigerant end of life recovery rate (%)	99	
B3: Materials replaced as part of repair (%)	10 (TM65 Assumption)	
C4: Percentage of product going to landfill (%)	30	



Telephone: 01707 282880 email: embodied.carbon@meuk.mee.com les.mitsubishielectric.co.uk





Mitsubishi Electric Living
Environmental Systems UK









UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe, Westgate Business Park, Ballymount, Dublin 24, Ireland. Telephone: (01) 419 8800 Fax: (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. @Mitsubishi Electric Europe 2023. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP-2088), R32 (GWP-675), R407C (GWP-1774), R134a (GWP-1430), R513A (GWP-631), R454B (GWP-631), R454B (GWP-1374), or R1234pt (GWP-7) or R123

Effective as of September 2023









