

PUMY-P250/300YBM2

CIBSE TM65 Embodied Carbon Mid-level Calculation

Assesment Date:

30th March 2023

Assessor / Organisation:

RI / Mitsubishi Electric LES UK

Contact:

embodied.carbon@meuk.mee.com

Embodied Carbon with 'Mid-level TM65 Calculation' Method (kg CO₂e) Total:

20,242

				Capacities (kW)*		28	33.5
Embodied Carbon Result per kW (kg CO ₂ e/kW):						723	604
	 	 	1 			Follow d'and	I O. h
2,182		18,059				Embodied Without R (kg CO ₂ e)	l Carbon - lefrigerant Leakage
						Embodied Refrigerar (kg CO₂e)	l Carbon - nt Leakage Only
- - !	5,000	10,000	15,000 	20,000	25,000	kg CO₂e	

PUMY-P250/300YBM2 - Product Information

Type of product	VRF Outdoor Unit
Capacity of equipment (kW)*	28/33.5
Product weight (kg)	192
Material breakdown for at least 95% of the product weight? (Y/N)	Υ
Service life of the product (years)	15
Type of refrigerant	R410A
Refrigerant GWP	2088
Energy consumption of the factory per unit of product (kWh)	9.48
Location of manufacture	Asia
Product Complexity	Category 3: High



^{*}Nominal cooling capacity conditions as per data book



PUMY-P250/300YBM2

CIBSE TM65 Embodied Carbon Mid-level Calculation

Embodied Carbon Results Breakdown (kg CO₂e)	
A1: Material extraction	1,290
A2: Transport	152
A3: Manufacturing	32
A4: Transport to Site	46
B1: Use	17,477
B3: Repair	153
C1: Deconstruction	583
C2: Transport	3
C3: Waste Processing	3
C4: Disposal	1

Ellibouled Carbon Results - Without Refligerant Leakage (kg CO2e)	
A1-C4 (excluding B1,C1)	1,679
A1-C4 with Buffer Factor (excluding B1, C1)	2.182

Embodied Carbon Result - Refrigerant Leakage Only (kg CO2e)

imbodied Carbon Pocults - without Pofrigorant Loakage (kg CO a)

B1 (Refrigerant leakage during use) + C1 (Refrigerant leakage end of life) 18,059

Assumptions			
A1: Material carbon coefficient source	TM65 Table 2.1 & The ICE Database		
B1: Refrigerant annual leakage rate (%)	6		
C1: Refrigerant end of life recovery rate (%)	97		
B3: Materials replaced as part of repair (%)	10 (TM65 Assumption)		
C4: Percentage of product going to landfill (%)	30		



Telephone: 01707 282880 email: embodied.carbon@meuk.mee.com les.mitsubishielectric.co.uk





Mitsubishi Electric Living
Environmental Systems UK









UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880 Fax: 01707 278881 IRELAND Mitsubishi Electric Europe, Westgate Business Park, Ballymount, Dublin 24, Ireland. Telephone: (01) 419 8800 Fax: (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. @Mitsubishi Electric Europe 2023. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only. Please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP-2088), R32 (GWP-675), R407C (GWP-1774), R134a (GWP-1430), R513A (GWP-631), R454B (GWP-631), R454B (GWP-1374), or R1234pt (GWP-7) or R123

Effective as of October 2023







