

# PUZ-M250-YKA2

### CIBSE TM65 Embodied Carbon Mid-level Calculation

Assesment Date: 2nd

2nd April 2024

**Assessor / Organisation:** 

RI / Mitsubishi Electric LES UK

Contact:

embodied.carbon@meuk.mee.com

# Embodied Carbon with 'Mid-level TM65 Calculation' Method (kg CO<sub>2</sub>e) Total:

4,721

|                   |         |         |          |          |                    |       | Capa  | icities (l | kW)*  |                               | 22  |  |
|-------------------|---------|---------|----------|----------|--------------------|-------|-------|------------|-------|-------------------------------|---|--|
| Embodie           | d Carbo | n Resul | t per kV | / (kg CO | <sub>2</sub> e/kW) | :     |       |            |       |                               | 215   |  |
|                   | <br>    | 1       | 1 1 1    | 1        | <br>               | 1     | 1     | 1          | 1     | 1<br>1<br>1<br>1<br>1         | Embodied Carbon - Without Refrigerant Leakage   |  |
|                   | 1,875   |         |          |          | 2,846              |       |       |            |       | <br> <br> <br> <br> <br> <br> | (kg CO <sub>2</sub> e)  Embodied Carbon - Refrigerant Leakage Only (kg CO <sub>2</sub> e) |  |
| <br> -<br> <br> - | 500     | 1,000   | 1,500    | 2,000    | 2,500              | 3,000 | 3,500 | 4,000      | 4,500 | 5,000                         | 0 kg CO <sub>2</sub> e  |  |

#### PUZ-M250-YKA2 - Product Information

| 22<br>138<br>Y   |
|------------------|
|                  |
| Υ                |
|                  |
| 15               |
| R32              |
| 675              |
| 25.14            |
| Asia             |
| Category 3: High |
|                  |

<sup>\*</sup>Nominal cooling capacity conditions as per data book



## PUZ-M250-YKA2

#### CIBSE TM65 Embodied Carbon Mid-level Calculation

| Embodied Carbon Results Breakdown (kg CO₂e) |       |
|---|-------|
| A1: Material extraction                     | 1,054 |
| A2: Transport                               | 109   |
| A3: Manufacturing                           | 106   |
| A4: Transport to Site                       | 33    |
| B1: Use                                     | 2,754 |
| B3: Repair                                  | 131   |
| C1: Deconstruction                          | 92    |
| C2: Transport                               | 2     |
| C3: Waste Processing                        | 7     |
| C4: Disposal                                | 0     |

| Linbouled Carbon Results - Without Reingerant Leakage (kg CO <sub>2</sub> e) |       |
|--|-------|
| A1-C4 (excluding B1,C1)  | 1,442 |
| A1-C4 with Buffer Factor (excluding B1, C1)                                  | 1.875 |

#### Embodied Carbon Result - Refrigerant Leakage Only (kg CO2e)

Embodied Carbon Pocults - without Pofrigorant Leakage (kg CO e)

B1 (Refrigerant leakage during use) + C1 (Refrigerant leakage end of life) 2,846

| Assumptions                                     |                                   |
|---|-----------------------------------|
| A1: Material carbon coefficient source          | TM65 Table 2.1 & The ICE Database |
| B1: Refrigerant annual leakage rate (%)         | 4                                 |
| C1: Refrigerant end of life recovery rate (%)   | 98                                |
| B3: Materials replaced as part of repair (%)    | 10 (TM65 Assumption)              |
| C4: Percentage of product going to landfill (%) | 30                                |



Telephone: 01707 282880

email: embodied.carbon@meuk.mee.com

Changes for the Better les.mitsubishielectric.co.uk













UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880 IRELAND Mitsubishi Electric Europe, Westgate Business Park, Ballymount, Dublin 24, Ireland. Telephone: (01) 419 8800 International code: (003531)

Country of origin: United Kingdom - Italy - Turkey - Japan - Thailand - Malaysia. @Mitsubishi Electric Europe 2024. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only and please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP-2088), R290 (GWP-30), R32 (GWP-675), R407C (GWP-1774), R134a (GWP-1430), R513A (GWP-631), R454B (GWP-44C) (GWP-148), R1234ze (GWP-7) or R1244 (GWP-1430), R513A (GWP-6750), R407C (GWP-1670) or R134a (GWP-1300).

Effective as of June 2024









