

PUZ-ZM200YKA2

CIBSE TM65 Embodied Carbon Mid-level Calculation

Assesment Date: 2nd Ap

2nd April 2024

Assessor / Organisation:

RI / Mitsubishi Electric LES UK

Contact:

embodied.carbon@meuk.mee.com

Embodied Carbon with 'Mid-level TM65 Calculation' Method (kg CO₂e) Total:

4,386

Embodied Carbon Result per kW (kg CO₂e/kW): 231 **Embodied Carbon -**Without Refrigerant Leakage (kg CO₂e) 1,749 2,637 **Embodied Carbon -**Refrigerant Leakage Only (kg CO₂e) 500 1,500 2,000 2,500 4,000 4,500 3,000 3,500 kg CO₂e

PUZ-ZM200YKA2 - Product Information

Type of product	Split Type Outdoor Unit
Capacity of equipment (kW)*	19
Product weight (kg)	137
Material breakdown for at least 95% of the product weight? (Y/N)	Υ
Service life of the product (years)	15
Type of refrigerant	R32
Refrigerant GWP	675
Energy consumption of the factory per unit of product (kWh)	25.14
Location of manufacture	UK
Product Complexity	Category 3: High

^{*}Nominal cooling capacity conditions as per data book



PUZ-ZM200YKA2

CIBSE TM65 Embodied Carbon Mid-level Calculation

Embodied Carbon Results Breakdown (kg CO₂e)	
A1: Material extraction	1,054
A2: Transport	109
A3: Manufacturing	50
A4: Transport to Site	1
B1: Use	2,552
B3: Repair	122
C1: Deconstruction	85
C2: Transport	2
C3: Waste Processing	7
C4: Disposal	0

Linbodied Carbon Results - Willout Refrigerant Leakage (kg CO ₂ e)	
A1-C4 (excluding B1,C1)	1,346
A1-C4 with Buffer Factor (excluding B1, C1)	1,749

Embodied Carbon Result - Refrigerant Leakage Only (kg CO2e)

Embodied Carbon Pocults - without Pofrigorant Leakage (kg CO e)

B1 (Refrigerant leakage during use) + C1 (Refrigerant leakage end of life) 2,637

Assumptions	
A1: Material carbon coefficient source	TM65 Table 2.1 & The ICE Database
B1: Refrigerant annual leakage rate (%)	4
C1: Refrigerant end of life recovery rate (%)	98
B3: Materials replaced as part of repair (%)	10 (TM65 Assumption)
C4: Percentage of product going to landfill (%)	30



Telephone: 01707 282880

email: embodied.carbon@meuk.mee.com

les.mitsubishielectric.co.uk













UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880 IRELAND Mitsubishi Electric Europe, Westgate Business Park, Ballymount, Dublin 24, Ireland. Telephone: (01) 419 8800 International code: (003531)

Country of origin: United Kingdom - Italy - Turkey - Japan - Thailand - Malaysia. @Mitsubishi Electric Europe 2024. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only and please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP-2088), R290 (GWP-30), R32 (GWP-675), R407C (GWP-1774), R134a (GWP-1430), R513A (GWP-631), R454B (GWP-44C) (GWP-148), R1234ze (GWP-7) or R1244 (GWP-1430), R513A (GWP-6750), R407C (GWP-1670) or R134a (GWP-1300).

Effective as of June 2024









