

# Ecodan R290

## Monobloc Air Source Heat Pump

**R290****Key Features:**

- A+++ heating efficiency (Range A+++ to D)
- Ultra quiet noise levels
- MELCloud Home enabled
- High water temperature of up to 75°C
- Fully electric source of heating and hot water

**Key Benefits:**

- Minimised energy consumption
- Flexible product placement
- Remote control, monitoring, maintenance and technical support
- Ideal for energy storage
- Zero carbon ready

**MELCloud  
HOME**

Manufactured in the UK



037-0033-20-01

red**dot** design award**ecodan**<sup>®</sup>  
Renewable Heating Technology

OUTDOOR UNIT		PUZ-WZ85V/YAA	PUZ-WZ100V/YAA	PUZ-WZ120V/YAA
HEAT PUMP SPACE HEATER - 55°C	ErP Rating	A++	A++	A++
	$\eta_s$	143%	141%	142%
	SCOP (MCS)	TBC	TBC	TBC
HEAT PUMP SPACE HEATER - 35°C	ErP Rating	A+++	A+++	A+++
	$\eta_s$	183%	189%	192%
	SCOP (MCS)	TBC	TBC	TBC
HEAT PUMP COMBINATION HEATER - Large Profile <sup>*1</sup>	ErP Rating	A+	A+	A+
	$\eta_{wh}$	137%	129%	129%
	Capacity (kW)	8.5	10.0	11.5
HEATING <sup>*2</sup> (A-7/W35)	COP	2.60	2.70	2.45
OPERATING AMBIENT TEMPERATURE (°C DB)		-25 ~ +46	-25 ~ +46	-25 ~ +46
MAXIMUM WATER OUTLET TEMPERATURE (°C)		75	75	75
SOUND DATA <sup>*3</sup>	Pressure Level at 1m (dBA)	40	40	40
	Power Level (dBA) <sup>*4</sup>	54	55	55
WATER DATA	Pipework Size (mm)	28	28	28
	Flow Rate (l/min)	27	34	34
DIMENSIONS (mm)	Width	1050	1050	1050
	Depth	480	480	480
	Height	1040	1040	1040
WEIGHT (kg)		103/117	120/131	120/131
ELECTRICAL DATA	Electrical Supply	220-240v, 50Hz / 400v	220-240v, 50Hz / 400v	220-240v, 50Hz / 400v
	Phase	Single / Three	Single / Three	Single / Three
	Nominal Running Current [MAX] (A) <sup>*5</sup>	21/12	28/12	35/12
	Fuse Rating - MCB Sizes (A) <sup>*6</sup>	25/16	32/16	40/16
REFRIGERANT CHARGE (kg) / CO <sub>2</sub> EQUIVALENT (t)		0.60 / 0.000012	0.82 / 0.0000164	0.82 / 0.0000164

## NOTES:

\*1 Combination with EHPT20X-MEHEW Cylinder

\*2 Under normal heating conditions at outdoor temp: -7°CDB / -8°CWB, outlet water temp 35°C, inlet water temp 30°C.

\*3 Under normal heating conditions at outdoor temp: 7°CDB / 6°CWB, outlet water temp 55°C, inlet water temp 47°C as tested to BS EN14511.

\*4 Sound power level tested to BS EN12102.

\*5 Under nominal heating conditions at outdoor temp: 7°C, outlet water temp: 35°C.

\*6 MCB Sizes BS EN60898-2 &amp; BS EN60947-2.

 $\eta_s$  is the seasonal space heating energy efficiency (SSHEE) $\eta_{wh}$  is the water heating energy efficiency




## PUZ-WZ85/100/120V/YAA DIMENSIONS

All dimensions (mm)


FRONT VIEW

TOP VIEW


SIDE VIEW




## PUZ-WZ85V/YAA CAPACITIES




## PUZ-WZ100V/YAA CAPACITIES







## PUZ-WZ120V/YAA CAPACITIES



## FLOW TEMPERATURE



Telephone: 01707 282880  
email: [heating@meuk.mee.com](mailto:heating@meuk.mee.com)  
[ecodan.co.uk](http://ecodan.co.uk)



UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880

IRELAND Mitsubishi Electric Europe, Plunkett House, Grange Castle Business Park, Nangor Road, Dublin 22, Ireland. Telephone: (00353) 1 4198800 Email: [sales.info@meir.mee.com](mailto:sales.info@meir.mee.com) Web: [les.mitsubishielectric.ie](http://les.mitsubishielectric.ie)

Country of origin: United Kingdom - Italy - Turkey - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2025. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only and please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2089), R32 (GWP:675), R407C (GWP:1774), R134a (GWP:1430), R513A (GWP:631), R454B (GWP:466), R515B (GWP:292), R454C (GWP:148), R1234ze (GWP:7) or R1234yf (GWP:4). \*These GWP values are based on Regulation (EU) No 517/2014 from IPCC 4th edition. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a hydrocarbon, R290 (GWP:0.02). \*These GWP values are based on IPCC 6th edition.

Effective as of April 2025

