

CP-500CM-L/R

Cooling Module



Enhance your home's protection against overheating with the **CP-500CM-L/R** cooling module - perfectly paired with the VL-500CZPVU-L/R-E and VL-520CZPVU-L/R-E residential Lossnay MVHR. This innovative system delivers tempered fresh air to help prevent overheating, supporting compliance with Part O building regulations.

Featuring a self-contained direct expansion system, advanced inverter technology, and lower GWP R32 refrigerant, it provides efficient cooling while meeting sustainability targets. Designed with Part O compliance at its core, it offers flexible activation temperatures, customisable capacity steps, and overshoot temperature controls, giving you total confidence in maintaining compliant indoor conditions.



Key Features & Benefits:

- Multi-zone activation connect up to four room temperature sensors to detect cooling requirements from different areas
- Low system height efficient use of space, maximising a home's floor area by allowing other services to be placed underneath the system
- Quiet performance enjoy a restful nights sleep even in the hottest summer's without the distraction of excess noise
- Eco-friendly & efficient the inverter-controlled compressor uses lower GWP R32 refrigerant, delivering powerful cooling while reducing environmental impact
- Hassle-free installation designed for simplicity, ensuring a smooth and efficient setup process
- Flexible airflow operational airflow as low as 50l/s allows precise capacity selection for each home's unique needs
- Behind-the-scenes control ensures adherence to Part O regulations, while preventing unnecessary end-user adjustments



MODEL		CP-500CM-L/R
OPERATION AIR FLOW (I/s)		50 - 140
DIMENSIONS (mm) (Width x Depth x Height)	Module	725 x 556 x 500
	System	725 x 586 x 1182
WEIGHT (kg)	Module	38
	System	77
REFRIGERANT		R32
REFRIGERANT CHARGE (kg)		0.55
COMPRESSOR MANAGEMENT		Inverter
SOUND POWER LEVEL (dB(A))		52.4
DUCT SPIGOT SIZE (mm)		160
ELECTRICAL SUPPLY		220-240V, 50Hz
MAX RUNNING CURRENT (A)		7.6
FUSE RATING (BS88) - HRC (A)		10

MODEL		Procon Overheat Thermostat (OHT)
DESCRIPTION		Manages activation and operation of cooling function. Reads internal temperature against set activation point, and manages interlock signals and system status
CONNECT TO		VL-500CZPVU-L/R-E and VL-520CZPVU-L/R-E CP-500CM-L/R
ELECTRICAL SUPPLY		Powered via Lossnay MVHR CN105
DIMENSIONS (mm)	Width x Depth x Height	190 x 42 x 180
WEIGHT (kg)		1.1
CONTROL	Temperature Input	Up to 4x 10K3A1*1
	Heating Interlock	VFC
	Manual Activation	VFC
	Block	VFC


Notes: *1 1 x 10K3A1 temperature sensor supplied with Procon OHT. VFC: Volt Free Contact

CP-500CM-L/R DIMENSIONS


COOLING MODULE


FRONT VIEW


UPPER VIEW



RIGHT SIDE VIEW







- 1.1 POWER SUPPLY
 1.2 CONNECTION TO PROCON OVERHEAT THERMOSTAT (OHT)
 2 CONDENSATE DRAIN
 3 0160mm MALE DUCT
 4 INSTALLATION TEMPLATE



793

Telephone: 01707 282880 email: air.conditioning@meuk.mee.com les.mitsubishielectric.co.uk





221

Mitsubishi Electric Livino Environmental Systems UK



Mitsubishi Electric Cooling and Heating UK







UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880 IRELAND Mitsubishi Electric Europe, Plunkett House, Grange Castle Business Park, Nangor Road, Dublin 22, Ireland. Telephone: (00353) 1 4198800 Email: sales.info@meir.mee.com Web: les.mitsubishielectric.ie

Country of origin: United Kingdom - Italy - Turkey - Japan - Thailand - Malaysia. @Mitsubishi Electric Europe 2025. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: The fuse rating is for guidance only and please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Missubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2088), R32 (GWP:675), R407C (GWP:1774), R134a (GWP:1430), R813A (GWP:631), R454B (GWP:468), R515B (GWP:292), R454C (GWP:148), R12342 (GWP:716), R1234y (GWP:48), R1342 (GWP:469), R5134 (GWP:

Effective as of September 2025









